

HS50 12R J Information



For Reference Only

Part Number HS50 12R J
Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 12 OHM 5% 50W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HS50 12R J Specifications

Manufacturer Part NumberHS50 12R JManufacturerOhmiteCategoryResistorsPackageAxial, BoxSeriesARCOL, HSResistance12 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.933" L x 0.559" W (49.10mm x 14.20mm)Height - Seated (Max)0.583" (14.80mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure RatePerport errors?		
Category Resistors Package Axial, Box Series ARCOL, HS Resistance 12 Ohms Tolerance ±5% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.933" L x 0.559" W (49.10mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Manufacturer Part Number	HS50 12R J
Chassis Mount Resistors Package Axial, Box Series ARCOL, HS Resistance 12 Ohms Tolerance ±5% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.933" L x 0.559" W (49.10mm x 14.20mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate - Charcology Axial, Box Failure Rate - Charcology Ax	Manufacturer	Ohmite
PackageAxial, BoxSeriesARCOL, HSResistance12 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.933" L x 0.559" W (49.10mm x 14.20mm)Height - Seated (Max)0.583" (14.80mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesARCOL, HSResistance12 OhmsTolerance±5%Power (Watts)50WCompositionWirewoundTemperature Coefficient±100ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.933" L x 0.559" W (49.10mm x 14.20mm)Height - Seated (Max)0.583" (14.80mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance 12 Ohms Tolerance ±5% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.933" L x 0.559" W (49.10mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Package	Axial, Box
Tolerance ±5% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.933" L x 0.559" W (49.10mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Series	ARCOL, HS
Power (Watts) 50W Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.933" L x 0.559" W (49.10mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Resistance	12 Ohms
Composition Wirewound Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.933" L x 0.559" W (49.10mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Tolerance	±5%
Temperature Coefficient ±100ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.933" L x 0.559" W (49.10mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Power (Watts)	50W
Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.933" L x 0.559" W (49.10mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.933" L x 0.559" W (49.10mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±100ppm/°C
Coating, Housing Type Mounting Feature Flanges Size / Dimension 1.933" L x 0.559" W (49.10mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Operating Temperature	-
Mounting Feature Size / Dimension 1.933" L x 0.559" W (49.10mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Package / Case Axial, Box Failure Rate -	Features	-
Size / Dimension 1.933" L x 0.559" W (49.10mm x 14.20mm) Height - Seated (Max) 0.583" (14.80mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Failure Rate 0.583" (14.80mm) Solder Lugs Axial, Box -	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	1.933" L x 0.559" W (49.10mm x 14.20mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.583" (14.80mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
Report crisis:		Report errors?

HS50 12R J Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HS50 12R J Payment Methods



















HS50 12R J Shipping Methods













If you have any question about HS50 12R J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com