



HS6T22SA Information



For Reference Only

Part Number HS6T22SA Manufacturer APEM Inc. Category Switches

Navigation Switches, Joystick

Description SWITCH THMBSTK PUSHBTN 100MA 30V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HS6T22SA Specifications

Manufacturer HS6T22SA Manufacturer APEM Inc. Category Switches Package - Series HS Type Thumbstick, 1 - Axis Actuator Type Pushbutton Switch Function 2-Way Directional, Center Select Functions, Extra - Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 100mA (DC) Voltage Rating - AC - Voltage Rating - DC 30V Contact Material - Contact Finish Silver Mounting Type Panel Mount Termination Style Wire Leads with Connector Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - Report errors?	•	
Category Switches Package - Series HS Type Thumbstick, 1 - Axis Actuator Type Pushbutton Switch Function 2-Way Directional, Center Select Functions, Extra - Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 100mA (DC) Voltage Rating - AC - Voltage Rating - DC 30V Contact Material - Contact Finish Silver Mounting Type Panel Mount Termination Style Wire Leads with Connector Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Manufacturer Part Number	HS6T22SA
Navigation Switches, Joystick Package Series HS Type Thumbstick, 1 - Axis Actuator Type Pushbutton Switch Function 2-Way Directional, Center Select Functions, Extra - Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 100mA (DC) Voltage Rating - AC Voltage Rating - DC 30V Contact Material - Contact Finish Silver Mounting Type Panel Mount Termination Style Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Ingress Protection P68/69K - Dust Tight, Water Resistant, Waterproof Features -	Manufacturer	APEM Inc.
Package-SeriesHSTypeThumbstick, 1 - AxisActuator TypePushbuttonSwitch Function2-Way Directional, Center SelectFunctions, Extra-OutputDigital (Mechanical Switch)Voltage - Supply-Current Rating100mA (DC)Voltage Rating - AC-Voltage Rating - DC30VContact Material-Contact FinishSilverMounting TypePanel MountTermination StyleWire Leads with ConnectorOperating Temperature-25°C ~ 80°CPanel Cutout DimensionsCircular - 25.02mm DiaIngress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofFeatures-	Category	Switches
Series HS Type Thumbstick, 1 - Axis Actuator Type Pushbutton Switch Function 2-Way Directional, Center Select Functions, Extra - Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 100mA (DC) Voltage Rating - AC - Voltage Rating - DC 30V Contact Material - Contact Finish Silver Mounting Type Panel Mount Termination Style Wire Leads with Connector Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -		Navigation Switches, Joystick
Type Thumbstick, 1 - Axis Actuator Type Pushbutton Switch Function 2-Way Directional, Center Select Functions, Extra - Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 100mA (DC) Voltage Rating - AC - Voltage Rating - DC 30V Contact Material - Contact Finish Silver Mounting Type Panel Mount Termination Style Wire Leads with Connector Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Package	-
Actuator Type Pushbutton Switch Function Switch Functions, Extra - Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 100mA (DC) Voltage Rating - AC - Voltage Rating - DC 30V Contact Material - Contact Finish Silver Mounting Type Panel Mount Termination Style Wire Leads with Connector Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Series	HS
Switch Function 2-Way Directional, Center Select Functions, Extra - Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 100mA (DC) Voltage Rating - AC - Voltage Rating - DC 30V Contact Material - Contact Finish Silver Mounting Type Panel Mount Termination Style Wire Leads with Connector Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Туре	Thumbstick, 1 - Axis
Functions, Extra Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 100mA (DC) Voltage Rating - AC Voltage Rating - DC 30V Contact Material - Contact Finish Silver Mounting Type Panel Mount Termination Style Wire Leads with Connector Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features - Digital (Mechanical Switch) - Digital (Mechanical	Actuator Type	Pushbutton
Output Digital (Mechanical Switch) Voltage - Supply - Current Rating 100mA (DC) Voltage Rating - AC - Voltage Rating - DC 30V Contact Material - Contact Finish Silver Mounting Type Panel Mount Termination Style Wire Leads with Connector Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Switch Function	2-Way Directional, Center Select
Voltage - Supply Current Rating 100mA (DC) Voltage Rating - AC - Voltage Rating - DC 30V Contact Material - Contact Finish Silver Mounting Type Panel Mount Termination Style Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection Features - 100mA (DC) - NomA (DC) No	Functions, Extra	-
Current Rating Voltage Rating - AC Voltage Rating - DC 30V Contact Material - Contact Finish Silver Mounting Type Panel Mount Termination Style Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features 100mA (DC) - 100mA (DC) 100mA	Output	Digital (Mechanical Switch)
Voltage Rating - AC Voltage Rating - DC 30V Contact Material - Contact Finish Mounting Type Panel Mount Termination Style Wire Leads with Connector Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Voltage - Supply	-
Voltage Rating - DC Contact Material Contact Finish Silver Mounting Type Panel Mount Termination Style Wire Leads with Connector Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Current Rating	100mA (DC)
Contact Material - Contact Finish Silver Mounting Type Panel Mount Termination Style Wire Leads with Connector Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Voltage Rating - AC	-
Contact Finish Mounting Type Panel Mount Termination Style Wire Leads with Connector Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Voltage Rating - DC	30V
Mounting Type Panel Mount Termination Style Wire Leads with Connector Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Contact Material	-
Termination Style Wire Leads with Connector Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Contact Finish	Silver
Operating Temperature -25°C ~ 80°C Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Mounting Type	Panel Mount
Panel Cutout Dimensions Circular - 25.02mm Dia Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Termination Style	Wire Leads with Connector
Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Features -	Operating Temperature	-25°C ~ 80°C
Features -	Panel Cutout Dimensions	Circular - 25.02mm Dia
	Ingress Protection	IP68/69K - Dust Tight, Water Resistant, Waterproof
Report errors?	Features	-
		Report errors

HS6T22SA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HS6T22SA Payment Methods



















HS6T22SA Shipping Methods













If you have any question about HS6T22SA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com