



HSA10220RJ Information

Part Number HSA10220RJ

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 220 OHM 5% 16W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HSA10220RJ Specifications

Manufacturer Part NumberHSA10220RJManufacturerTE Connectivity Passive ProductCategoryResistorsPackageAxial, BoxSeriesHS, CGSResistance220 OhmsTolerance±5%Power (Watts)16WCompositionWirewoundTemperature Coefficient±30ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.827" L x 0.827" W (21.00mm x 21.00mm)Height - Seated (Max)0.433" (11.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		
CategoryResistorsPackageAxial, BoxSeriesHS, CGSResistance220 OhmsTolerance±5%Power (Watts)16WCompositionWirewoundTemperature Coefficient±30ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.827" L x 0.827" W (21.00mm x 21.00mm)Height - Seated (Max)0.433" (11.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer Part Number	HSA10220RJ
Chassis Mount Resistors Package Axial, Box Series HS, CGS Resistance 220 Ohms Tolerance ±5% Power (Watts) 16W Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.827" L x 0.827" W (21.00mm x 21.00mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Manufacturer	TE Connectivity Passive Product
Package Axial, Box Series HS, CGS Resistance 220 Ohms Tolerance ±5% Power (Watts) 16W Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.827" L x 0.827" W (21.00mm x 21.00mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Category	Resistors
Series HS, CGS Resistance 220 Ohms Tolerance ±5% Power (Watts) 16W Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.827" L x 0.827" W (21.00mm x 21.00mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -		Chassis Mount Resistors
Resistance 220 Ohms Tolerance ±5% Power (Watts) 16W Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.827" L x 0.827" W (21.00mm x 21.00mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Package	Axial, Box
Tolerance ±5% Power (Watts) 16W Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.827" L x 0.827" W (21.00mm x 21.00mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Series	HS, CGS
Power (Watts) Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.827" L x 0.827" W (21.00mm x 21.00mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Resistance	220 Ohms
Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.827" L x 0.827" W (21.00mm x 21.00mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Tolerance	±5%
Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.827" L x 0.827" W (21.00mm x 21.00mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Power (Watts)	16W
Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.827" L x 0.827" W (21.00mm x 21.00mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Package / Case Axial, Box Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.827" L x 0.827" W (21.00mm x 21.00mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±30ppm/°C
Coating, Housing Type Mounting Feature Flanges Size / Dimension 0.827" L x 0.827" W (21.00mm x 21.00mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Operating Temperature	-55°C ~ 200°C
Mounting Feature Size / Dimension 0.827" L x 0.827" W (21.00mm x 21.00mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Package / Case Axial, Box Failure Rate -	Features	-
Size / Dimension 0.827" L x 0.827" W (21.00mm x 21.00mm) Height - Seated (Max) 0.433" (11.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Failure Rate 0.433" (11.00mm) Solder Lugs Axial, Box -	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	0.827" L x 0.827" W (21.00mm x 21.00mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.433" (11.00mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

HSA10220RJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HSA10220RJ Payment Methods





















HSA10220RJ Shipping Methods













If you have any question about HSA10220RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com