



HSC1001K2J Information

Part Number HSC1001K2J

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 1.2K OHM 5% 100W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HSC1001K2J Specifications

Manufacturer Part NumberHSC1001K2JManufacturerTE Connectivity Passive ProductCategoryResistorsPackageAxial, BoxSeriesHS, CGSResistance1.2 kOhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±30ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.579" L x 1.870" W (65.50mm x 47.50mm)Height - Seated (Max)1.024" (26.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		
CategoryResistorsPackageAxial, BoxSeriesHS, CGSResistance1.2 kOhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±30ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.579" L x 1.870" W (65.50mm x 47.50mm)Height - Seated (Max)1.024" (26.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer Part Number	HSC1001K2J
Chassis Mount Resistors Package Axial, Box Series HS, CGS Resistance 1.2 kOhms Tolerance ±5% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Manufacturer	TE Connectivity Passive Product
PackageAxial, BoxSeriesHS, CGSResistance1.2 kOhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±30ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.579" L x 1.870" W (65.50mm x 47.50mm)Height - Seated (Max)1.024" (26.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesHS, CGSResistance1.2 kOhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±30ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.579" L x 1.870" W (65.50mm x 47.50mm)Height - Seated (Max)1.024" (26.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance1.2 kOhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±30ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.579" L x 1.870" W (65.50mm x 47.50mm)Height - Seated (Max)1.024" (26.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance ±5% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Series	HS, CGS
Power (Watts) Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Resistance	1.2 kOhms
Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Tolerance	±5%
Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Power (Watts)	100W
Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Package / Case Axial, Box Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±30ppm/°C
Coating, Housing Type Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Operating Temperature	-55°C ~ 200°C
Mounting Feature Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Package / Case Axial, Box Failure Rate -	Features	-
Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate 1.024" (26.00mm) Solder Lugs	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	2.579" L x 1.870" W (65.50mm x 47.50mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	1.024" (26.00mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

HSC1001K2J Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HSC1001K2J Payment Methods



















HSC1001K2J Shipping Methods













If you have any question about HSC1001K2J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com