



HSC100270RJ Information

Heisener.com

Part Number HSC100270RJ

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 270 OHM 5% 100W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HSC100270RJ Specifications

Manufacturer Part NumberHSC100270RJManufacturerTE Connectivity Passive ProductCategoryResistorsPackageAxial, BoxSeriesHS, CGSResistance270 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±30ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.579" L x 1.870" W (65.50mm x 47.50mm)Height - Seated (Max)1.024" (26.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		
CategoryResistorsPackageAxial, BoxSeriesHS, CGSResistance270 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±30ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.579" L x 1.870" W (65.50mm x 47.50mm)Height - Seated (Max)1.024" (26.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer Part Number	HSC100270RJ
Chassis Mount Resistors Package Axial, Box Series HS, CGS Resistance 270 Ohms Tolerance ±5% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate	Manufacturer	TE Connectivity Passive Product
PackageAxial, BoxSeriesHS, CGSResistance270 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±30ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.579" L x 1.870" W (65.50mm x 47.50mm)Height - Seated (Max)1.024" (26.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesHS, CGSResistance270 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±30ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.579" L x 1.870" W (65.50mm x 47.50mm)Height - Seated (Max)1.024" (26.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance270 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±30ppm/°COperating Temperature-55°C ~ 200°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension2.579" L x 1.870" W (65.50mm x 47.50mm)Height - Seated (Max)1.024" (26.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance ±5% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Series	HS, CGS
Power (Watts) Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Package / Case Axial, Box Failure Rate -	Resistance	270 Ohms
Composition Wirewound Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Tolerance	±5%
Temperature Coefficient ±30ppm/°C Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Power (Watts)	100W
Operating Temperature -55°C ~ 200°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Package / Case Axial, Box Failure Rate - Size / Dimension - Solder Lugs - Failure Rate	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±30ppm/°C
Coating, Housing Type Mounting Feature Flanges Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Operating Temperature	-55°C ~ 200°C
Mounting Feature Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Package / Case Axial, Box Failure Rate -	Features	-
Size / Dimension 2.579" L x 1.870" W (65.50mm x 47.50mm) Height - Seated (Max) 1.024" (26.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate 1.024" (26.00mm) Solder Lugs	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	2.579" L x 1.870" W (65.50mm x 47.50mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	1.024" (26.00mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

HSC100270RJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HSC100270RJ Payment Methods



















HSC100270RJ Shipping Methods













If you have any question about HSC100270RJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com