



# **HSC2506R8J Information**

Heisener.com

Part Number HSC2506R8J

Manufacturer TE Connectivity Passive Product

**Category** Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 6.8 OHM 5% 250W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **HSC2506R8J Specifications**

Manufacturer Part NumberHSC2506R8JManufacturerTE Connectivity Passive ProductCategoryResistorsChassis Mount ResistorsPackageAxial, BoxSeriesHS, CGSResistance6.8 OhmsTolerance±5%Power (Watts)250WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 200°C		
Category  Resistors  Chassis Mount Resistors  Package Axial, Box  Series HS, CGS  Resistance 6.8 Ohms  Tolerance ±5%  Power (Watts) 250W  Composition Wirewound  Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 200°C		
Chassis Mount Resistors  Package Axial, Box  Series HS, CGS  Resistance 6.8 Ohms  Tolerance ±5%  Power (Watts) 250W  Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 200°C	ty Passive Product	
PackageAxial, BoxSeriesHS, CGSResistance $6.8 \text{ Ohms}$ Tolerance $\pm 5\%$ Power (Watts) $250W$ CompositionWirewoundTemperature Coefficient $\pm 50 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 200^{\circ}\text{C}$		
SeriesHS, CGSResistance $6.8 \text{ Ohms}$ Tolerance $\pm 5\%$ Power (Watts) $250W$ CompositionWirewoundTemperature Coefficient $\pm 50 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 200^{\circ}\text{C}$	Resistors	
Resistance $6.8 \text{ Ohms}$ Tolerance $\pm 5\%$ Power (Watts) $250W$ CompositionWirewoundTemperature Coefficient $\pm 50 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 200^{\circ}\text{C}$		
Tolerance $\pm 5\%$ Power (Watts) $250W$ CompositionWirewoundTemperature Coefficient $\pm 50 \mathrm{ppm/^{\circ}C}$ Operating Temperature $-55^{\circ}\mathrm{C} \sim 200^{\circ}\mathrm{C}$		
Power (Watts) 250W  Composition Wirewound  Temperature Coefficient $\pm 50 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 200^{\circ}\text{C}$		
Composition Wirewound  Temperature Coefficient $\pm 50 \text{ppm}/^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 200^{\circ}\text{C}$		
Temperature Coefficient $\pm 50 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 200^{\circ}\text{C}$		
Operating Temperature $-55^{\circ}\text{C} \sim 200^{\circ}\text{C}$		
Features -		
Coating, Housing Type Aluminum		
Mounting Feature Flanges		
Size / Dimension 4.291" L x 2.874" W (109.00mm x 73.00mm)	74" W (109.00mm x 73.0	n)
Height - Seated (Max) 1.650" (42.00mm)	nm)	
Lead Style Terminal Screw Type	w Type	
Package / Case Axial, Box		
Failure Rate -		
Report error		Report errors?

#### **HSC2506R8J Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **HSC2506R8J Payment Methods**



















## **HSC2506R8J Shipping Methods**













If you have any question about HSC2506R8J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com