

HSCDAND015PASA3

HSCDAND015PASA3 Information



For Reference Only

Part Number HSCDAND015PASA3

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRES 15PSI ABSO 3.3V DIP **Package** 8-DIP (0.524", 13.30mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HSCDAND015PASA3 Specifications

Manufacturer Part NumberHSCDAND015PASA3ManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage8-DIP (0.524", 13.30mm), Top PortSeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top PortSupplier Device Package8-DIP			
Category Sensors, Transducers Package 8-DIP (0.524", 13.30mm), Top Port Series TruStability? HSC Pressure Type Absolute Operating Pressure 15 PSI (103.42 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Manufacturer Part Number	HSCDAND015PASA3	
Package 8-DIP (0.524", 13.30mm), Top Port Series TruStability? HSC Pressure Type Absolute Operating Pressure 15 PSI (103.42 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature - 20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions	
Package8-DIP (0.524", 13.30mm), Top PortSeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top PortSupplier Device Package8-DIP	Category	Sensors, Transducers	
Series Trustability? HSC Pressure Type Absolute Operating Pressure 15 PSI (103.42 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package		Pressure Sensors, Transducers	
Pressure Type Absolute Operating Pressure 15 PSI (103.42 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Package	8-DIP (0.524", 13.30mm), Top Port	
Operating Pressure 15 PSI (103.42 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package	Series	TruStability? HSC	
Output Type Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Pressure Type	Absolute	
Output Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Operating Pressure	15 PSI (103.42 kPa)	
Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package	Output Type	SPI	
Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package	Output	12 b	
Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Accuracy	±0.25%	
Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Voltage - Supply	3 V ~ 3.6 V	
Features Amplified Output, Temperature Compensated PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Port Size	Male - 0.19" (4.93mm) Tube	
Termination Style PC Pin Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Port Style	Barbed	
Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Features	Amplified Output, Temperature Compensated	
Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Termination Style	PC Pin	
Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Maximum Pressure	30 PSI (206.84 kPa)	
Supplier Device Package 8-DIP	Operating Temperature	-20°C ~ 85°C	
	Package / Case	8-DIP (0.524", 13.30mm), Top Port	
Report errors?	Supplier Device Package	8-DIP	
			Report errors?

HSCDAND015PASA3 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HSCDAND015PASA3 Payment Methods



















HSCDAND015PASA3 Shipping Methods













If you have any question about HSCDAND015PASA3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com