

HSCDANN150PG2A5

HSCDANN150PG2A5 Information



For Reference Only

Part Number HSCDANN150PG2A5

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESS 150PSI GAUGE 5V DIP

Package 8-DIP (0.524", 13.30mm), Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HSCDANN150PG2A5 Specifications

Manufacturer Part NumberHSCDANN150PG2A5ManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage8-DIP (0.524", 13.30mm), Top PortSeriesTruStability? HSCPressure TypeVented GaugeOperating Pressure150 PSI (1034.21 kPa)Output Type12COutput12 bAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top PortSupplier Device Package8-DIP			
Category Sensors, Transducers Package 8-DIP (0.524", 13.30mm), Top Port Series TruStability? HSC Pressure Type Vented Gauge Operating Pressure 150 PSI (1034.21 kPa) Output Type 12C Output 12 b Accuracy ±0.25% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature 20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Manufacturer Part Number	HSCDANN150PG2A5	
Package 8-DIP (0.524", 13.30mm), Top Port Series TruStability? HSC Pressure Type Vented Gauge Operating Pressure 150 PSI (1034.21 kPa) Output Type 12C Output 12 b Accuracy ±0.25% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions	
Package8-DIP (0.524", 13.30mm), Top PortSeriesTruStability? HSCPressure TypeVented GaugeOperating Pressure150 PSI (1034.21 kPa)Output TypeI2COutput12 bAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top PortSupplier Device Package8-DIP	Category	Sensors, Transducers	
SeriesTruStability? HSCPressure TypeVented GaugeOperating Pressure150 PSI (1034.21 kPa)Output Type12COutput12 bAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top PortSupplier Device Package8-DIP		Pressure Sensors, Transducers	
Pressure TypeVented GaugeOperating Pressure150 PSI (1034.21 kPa)Output Type12COutput12 bAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure250 PSI (1723.69 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Top PortSupplier Device Package8-DIP	Package	8-DIP (0.524", 13.30mm), Top Port	
Operating Pressure 150 PSI (1034.21 kPa) Output Type 12C Output 12 b Accuracy ±0.25% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package	Series	TruStability? HSC	
Output Type I2C Output 12 b Accuracy ±0.25% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Pressure Type	Vented Gauge	
Output Accuracy ±0.25% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package	Operating Pressure	150 PSI (1034.21 kPa)	
Accuracy ±0.25% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package	Output Type	12C	
Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package	Output	12 b	
Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Accuracy	±0.25%	
Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Voltage - Supply	4.75 V ~ 5.25 V	
Features Amplified Output, Temperature Compensated PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package	Port Size	Male - 0.19" (4.93mm) Tube	
Termination Style PC Pin Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Port Style	Barbed	
Maximum Pressure 250 PSI (1723.69 kPa) Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Features	Amplified Output, Temperature Compensated	
Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Termination Style	PC Pin	
Package / Case 8-DIP (0.524", 13.30mm), Top Port Supplier Device Package 8-DIP	Maximum Pressure	250 PSI (1723.69 kPa)	
Supplier Device Package 8-DIP	Operating Temperature	-20°C ~ 85°C	
	Package / Case	8-DIP (0.524", 13.30mm), Top Port	
Report errors?	Supplier Device Package	8-DIP	
Topot district			Report errors?

HSCDANN150PG2A5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HSCDANN150PG2A5 Payment Methods



















HSCDANN150PG2A5 Shipping Methods













If you have any question about HSCDANN150PG2A5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com