

HSCDRND2.5BGSA3

HSCDRND2.5BGSA3 Information



For Reference Only

Part Number HSCDRND2.5BGSA3

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionBRD MNT PRESSURE SENSORS**Package**8-DIP (0.524", 13.30mm), Side Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HSCDRND2.5BGSA3 Specifications

Manufacturer Part Number Manufacturer Category Sensors, Transducers Pressure Sensors, Transducers Package 8-DIP (0.524", 13.30mm), Side Port Series TruStability? HSC Pressure Type Vented Gauge Operating Pressure 36.26 PSI (250 kPa) Output Type Output 12 b Accuracy ±0.25% Voltage - Supply Port Size Male - 0.08" (1.93mm) Tube Port Style Features Amplified Output, Temperature Compensated Permination Style Maximum Pressure 116.03 PSI (800 kPa) Operating Temperature -20°C ~ 85°C Package / Case Supplier Device Package Report errors?		
Category Sensors, Transducers Package 8-DIP (0.524", 13.30mm), Side Port Series TruStability? HSC Pressure Type Vented Gauge Operating Pressure 36.26 PSI (250 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 116.03 PSI (800 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Manufacturer Part Number	HSCDRND2.5BGSA3
Package 8-DIP (0.524", 13.30mm), Side Port Series TruStability? HSC Pressure Type Vented Gauge Operating Pressure 36.26 PSI (250 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 116.03 PSI (800 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 8-DIP (0.524", 13.30mm), Side Port Series TruStability? HSC Pressure Type Vented Gauge Operating Pressure 36.26 PSI (250 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 116.03 PSI (800 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Category	Sensors, Transducers
SeriesTruStability? HSCPressure TypeVented GaugeOperating Pressure36.26 PSI (250 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.08" (1.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure116.03 PSI (800 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Side PortSupplier Device Package8-DIP		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure $36.26 \text{ PSI } (250 \text{ kPa})$ Output TypeSPIOutput 12 b Accuracy $\pm 0.25\%$ Voltage - Supply $3 \text{ V} \sim 3.6 \text{ V}$ Port SizeMale - 0.08 " (1.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure $116.03 \text{ PSI } (800 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8-\text{DIP} (0.524^{\circ}, 13.30\text{mm}), \text{ Side Port}$ Supplier Device Package $8-\text{DIP}$	Package	8-DIP (0.524", 13.30mm), Side Port
Operating Pressure 36.26 PSI (250 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 116.03 PSI (800 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package	Series	TruStability? HSC
Output Type Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 116.03 PSI (800 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Pressure Type	Vented Gauge
Output Accuracy ±0.25% Voltage - Supply Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 116.03 PSI (800 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package	Operating Pressure	36.26 PSI (250 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $3 \text{ V} \sim 3.6 \text{ V}$ Port Size $Male - 0.08'' (1.93\text{mm}) \text{ Tube}$ Port Style $Barbed$ Features $Amplified Output, Temperature Compensated$ Termination Style $PC Pin$ Maximum Pressure $116.03 \text{ PSI } (800 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8-\text{DIP} (0.524'', 13.30\text{mm}), \text{Side Port}$ Supplier Device Package $8-\text{DIP}$	Output Type	SPI
Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 116.03 PSI (800 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package	Output	12 b
Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 116.03 PSI (800 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package	Accuracy	±0.25%
Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 116.03 PSI (800 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package	Voltage - Supply	3 V ~ 3.6 V
Features Amplified Output, Temperature Compensated PC Pin Maximum Pressure 116.03 PSI (800 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package	Port Size	Male - 0.08" (1.93mm) Tube
Termination Style PC Pin Maximum Pressure 116.03 PSI (800 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Port Style	Barbed
Maximum Pressure 116.03 PSI (800 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Features	Amplified Output, Temperature Compensated
Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Termination Style	PC Pin
Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Maximum Pressure	116.03 PSI (800 kPa)
Supplier Device Package 8-DIP	Operating Temperature	-20°C ~ 85°C
	Package / Case	8-DIP (0.524", 13.30mm), Side Port
Report errors?	Supplier Device Package	8-DIP
		Report errors?

HSCDRND2.5BGSA3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HSCDRND2.5BGSA3 Payment Methods



















HSCDRND2.5BGSA3 Shipping Methods













If you have any question about HSCDRND2.5BGSA3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com