

HSCDRNN001BASA3

HSCDRNN001BASA3 Information



For Reference Only

Part Number HSCDRNN001BASA3

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionBRD MNT PRESSURE SENSORS**Package**8-DIP (0.524", 13.30mm), Side Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HSCDRNN001BASA3 Specifications

Manufacturer Part NumberHSCDRNN001BASA3ManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage8-DIP (0.524", 13.30mm), Side PortSeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure14.5 PSI (100 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.08" (1.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC Pin
CategorySensors, TransducersPackage8-DIP (0.524", 13.30mm), Side PortSeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure14.5 PSI (100 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.08" (1.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC Pin
Pressure Sensors, Transducers Package 8-DIP (0.524", 13.30mm), Side Port Series TruStability? HSC Pressure Type Absolute Operating Pressure 14.5 PSI (100 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin
Package8-DIP (0.524", 13.30mm), Side PortSeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure14.5 PSI (100 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.08" (1.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC Pin
SeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure14.5 PSI (100 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.08" (1.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC Pin
Pressure Type Absolute Operating Pressure 14.5 PSI (100 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin
Operating Pressure Output Type SPI Output 12 b Accuracy 40.25% Voltage - Supply Port Size Male - 0.08" (1.93mm) Tube Port Style Features Amplified Output, Temperature Compensated PC Pin
Output TypeSPIOutput 12 b Accuracy $\pm 0.25\%$ Voltage - Supply $3 \text{ V} \sim 3.6 \text{ V}$ Port SizeMale - 0.08 " (1.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC Pin
Output 12 b Accuracy $\pm 0.25\%$ Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08 " (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin
Accuracy $\pm 0.25\%$ Voltage - Supply $3 \text{ V} \sim 3.6 \text{ V}$ Port Size $\text{Male} - 0.08'' (1.93\text{mm}) \text{ Tube}$ Port Style Barbed Features $\text{Amplified Output, Temperature Compensated}$ Termination Style PC Pin
Voltage - Supply $3 \text{ V} \sim 3.6 \text{ V}$ Port Size $\text{Male} - 0.08'' (1.93\text{mm}) \text{ Tube}$ Port Style Barbed Features $\text{Amplified Output, Temperature Compensated}$ Termination Style PC Pin
Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin
Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin
Features Amplified Output, Temperature Compensated Termination Style PC Pin
Termination Style PC Pin
20.04.707 (200.17)
Maximum Pressure 29.01 PSI (200 kPa)
Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Package / Case 8-DIP (0.524", 13.30mm), Side Port
Supplier Device Package 8-DIP
Report errors?

HSCDRNN001BASA3 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HSCDRNN001BASA3 Payment Methods



















HSCDRNN001BASA3 Shipping Methods













If you have any question about HSCDRNN001BASA3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com