

HSCDRNN030PA4A3

HSCDRNN030PA4A3 Information



For Reference Only

Part Number HSCDRNN030PA4A3

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionBRD MNT PRESSURE SENSORSPackage8-DIP (0.524", 13.30mm), Side Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HSCDRNN030PA4A3 Specifications

Manufacturer Part Number HSCDRNN030PA4A3 Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 8-DIP (0.524", 13.30mm), Side Port Series TruStability? HSC Pressure Type Absolute Operating Pressure 30 PSI (206.84 kPa) Output Type I2C Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP			
Category Sensors, Transducers Package 8-DIP (0.524", 13.30mm), Side Port Series TruStability? HSC Pressure Type Absolute Operating Pressure 30 PSI (206.84 kPa) Output Type 12C Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Manufacturer Part Number	HSCDRNN030PA4A3	
Package 8-DIP (0.524", 13.30mm), Side Port Series TruStability? HSC Pressure Type Absolute Operating Pressure 30 PSI (206.84 kPa) Output Type 12C Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature - 20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions	
Package8-DIP (0.524", 13.30mm), Side PortSeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure30 PSI (206.84 kPa)Output TypeI2COutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort SizeMale - 0.08" (1.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StylePC PinMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-DIP (0.524", 13.30mm), Side PortSupplier Device Package8-DIP	Category	Sensors, Transducers	
Series Trustability? HSC Pressure Type Absolute Operating Pressure 30 PSI (206.84 kPa) Output Type I2C Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Fermination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package		Pressure Sensors, Transducers	
Pressure Type 30 PSI (206.84 kPa) Output Type 12C Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port	Package	8-DIP (0.524", 13.30mm), Side Port	
Operating Pressure 30 PSI (206.84 kPa) Output Type 12C Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package	Series	TruStability? HSC	
Output Type Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package	Pressure Type	Absolute	
Output Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package	Operating Pressure	30 PSI (206.84 kPa)	
Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package	Output Type	I2C	
Voltage - Supply 3 V ~ 3.6 V Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package	Output	12 b	
Port Size Male - 0.08" (1.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Accuracy	±0.25%	
Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Voltage - Supply	3 V ~ 3.6 V	
Features Amplified Output, Temperature Compensated PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Port Size	Male - 0.08" (1.93mm) Tube	
Termination Style PC Pin Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Port Style	Barbed	
Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Features	Amplified Output, Temperature Compensated	
Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Termination Style	PC Pin	
Package / Case 8-DIP (0.524", 13.30mm), Side Port Supplier Device Package 8-DIP	Maximum Pressure	60 PSI (413.69 kPa)	
Supplier Device Package 8-DIP	Operating Temperature	-20°C ~ 85°C	
	Package / Case	8-DIP (0.524", 13.30mm), Side Port	
Report errors?	Supplier Device Package	8-DIP	
			Report errors?

HSCDRNN030PA4A3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HSCDRNN030PA4A3 Payment Methods



















HSCDRNN030PA4A3 Shipping Methods













If you have any question about HSCDRNN030PA4A3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com