

HSCMAND150PASA5

HSCMAND150PASA5 Information



For Reference Only

Part Number HSCMAND150PASA5

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description BRD MNT PRESSURE SENSORS

Package 8-SMD, J-Lead, Top Port

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HSCMAND150PASA5 Specifications

Manufacturer Part NumberHSCMAND150PASA5ManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage8-SMD, J-Lead, Top PortSeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure150 PSI (1034.21 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface Mount		
CategorySensors, TransducersPackage8-SMD, J-Lead, Top PortSeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure150 PSI (1034.21 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface Mount	Manufacturer Part Number	HSCMAND150PASA5
Package 8-SMD, J-Lead, Top Port Series TruStability? HSC Pressure Type Absolute Operating Pressure 150 PSI (1034.21 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style SMD, J-Lead, Top Port TruStability? HSC 1ruStability? HSC 2ruStability? HSC 4ruStability? HSC 1stability? H	Manufacturer	Honeywell Sensing and Productivity Solutions
Package8-SMD, J-Lead, Top PortSeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure150 PSI (1034.21 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface Mount	Category	Sensors, Transducers
SeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure150 PSI (1034.21 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 0.19" (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface Mount		Pressure Sensors, Transducers
Pressure Type Absolute Operating Pressure 150 PSI (1034.21 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount	Package	8-SMD, J-Lead, Top Port
Operating Pressure 150 PSI (1034.21 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply Port Size Male - 0.19" (4.93mm) Tube Port Style Features Amplified Output, Temperature Compensated Termination Style 150 PSI (1034.21 kPa) SPI 12 b 4.75 V ~ 5.25 V Annual Port Style Barbed Features Amplified Output, Temperature Compensated Surface Mount	Series	TruStability? HSC
Output TypeSPIOutput 12 b Accuracy $\pm 0.25\%$ Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Port SizeMale - 0.19 " (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface Mount	Pressure Type	Absolute
Output 12 b Accuracy $\pm 0.25\%$ Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount	Operating Pressure	150 PSI (1034.21 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Port Size $\text{Male - 0.19" (4.93 mm) Tube}$ Port Style Barbed Features $\text{Amplified Output, Temperature Compensated}$ Termination Style Surface Mount	Output Type	SPI
Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Port SizeMale - 0.19 " (4.93mm) TubePort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface Mount	Output	12 b
Port Size Male - 0.19" (4.93mm) Tube Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount	Accuracy	±0.25%
Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount	Voltage - Supply	4.75 V ~ 5.25 V
Features Amplified Output, Temperature Compensated Termination Style Surface Mount	Port Size	Male - 0.19" (4.93mm) Tube
Termination Style Surface Mount	Port Style	Barbed
·	Features	Amplified Output, Temperature Compensated
	Termination Style	Surface Mount
Maximum Pressure 250 PSI (1723.69 kPa)	Maximum Pressure	250 PSI (1723.69 kPa)
Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Operating Temperature	-20°C ~ 85°C
Package / Case 8-SMD, J-Lead, Top Port	Package / Case	8-SMD, J-Lead, Top Port
Supplier Device Package 8-SMD	Supplier Device Package	8-SMD
Report errors		Report errors?

HSCMAND150PASA5 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HSCMAND150PASA5 Payment Methods



















HSCMAND150PASA5 Shipping Methods













If you have any question about HSCMAND150PASA5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com