

HSCMNND600MDSA3

HSCMNND600MDSA3 Information



For Reference Only

Part Number HSCMNND600MDSA3

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description BRD MNT PRESSURE SENSORS

Package 8-SMD, J-Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HSCMNND600MDSA3 Specifications

Manufacturer Part Number HSCMNND600MDSA3 Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 8-SMD, J-Lead Series TruStability? HSC Pressure Type Differential Operating Pressure ±8.7 PSI (±60 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size - Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±29.01 PSI (±200 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD Report errors?		
CategorySensors, TransducersPackage8-SMD, J-LeadSeriesTruStability? HSCPressure TypeDifferentialOperating Pressure±8.7 PSI (±60 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort Size-Port StyleNo PortFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure±29.01 PSI (±200 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-LeadSupplier Device Package8-SMD	Manufacturer Part Number	HSCMNND600MDSA3
Package 8-SMD, J-Lead Series TruStability? HSC Pressure Type Differential Operating Pressure	Manufacturer	Honeywell Sensing and Productivity Solutions
Package8-SMD, J-LeadSeriesTruStability? HSCPressure TypeDifferentialOperating Pressure±8.7 PSI (±60 kPa)Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort Size-Port StyleNo PortFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure±29.01 PSI (±200 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-LeadSupplier Device Package8-SMD	Category	Sensors, Transducers
Series Trustability? HSC Pressure Type Differential Operating Pressure ±8.7 PSI (±60 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size - Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±29.01 PSI (±200 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package		Pressure Sensors, Transducers
Pressure Type Differential Operating Pressure ±8.7 PSI (±60 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size - Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±29.01 PSI (±200 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package	Package	8-SMD, J-Lead
Operating Pressure ±8.7 PSI (±60 kPa) Output Type SPI Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size - Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±29.01 PSI (±200 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Series	TruStability? HSC
Output TypeSPIOutput12 bAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort Size-Port StyleNo PortFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure±29.01 PSI (±200 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-LeadSupplier Device Package8-SMD	Pressure Type	Differential
Output 12 b Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size - Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±29.01 PSI (±200 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Operating Pressure	±8.7 PSI (±60 kPa)
Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size - Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±29.01 PSI (±200 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Output Type	SPI
Voltage - Supply 3 V ~ 3.6 V Port Size - Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±29.01 PSI (±200 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Output	12 b
Port Size - No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±29.01 PSI (±200 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Accuracy	±0.25%
Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure ±29.01 PSI (±200 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Voltage - Supply	3 V ~ 3.6 V
Features Amplified Output, Temperature Compensated Termination Style Surface Mount ±29.01 PSI (±200 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Port Size	-
Termination Style Surface Mount Maximum Pressure ±29.01 PSI (±200 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Port Style	No Port
Maximum Pressure ±29.01 PSI (±200 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Features	Amplified Output, Temperature Compensated
Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Termination Style	Surface Mount
Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Maximum Pressure	±29.01 PSI (±200 kPa)
Supplier Device Package 8-SMD	Operating Temperature	-20°C ~ 85°C
	Package / Case	8-SMD, J-Lead
Report errors?	Supplier Device Package	8-SMD
		Report errors?

HSCMNND600MDSA3 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HSCMNND600MDSA3 Payment Methods





















HSCMNND600MDSA3 Shipping Methods













If you have any question about HSCMNND600MDSA3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com