

# **HSCMNNN015PA2A5**

#### **HSCMNNN015PA2A5 Information**



For Reference Only

Part Number HSCMNNN015PA2A5

Manufacturer Honeywell Sensing and Productivity Solutions

**Category** Sensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR PRES 5V SMD

Package 8-SMD, J-Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **HSCMNNN015PA2A5** Specifications

Manufacturer Part NumberHSCMNNN015PA2A5ManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage8-SMD, J-LeadSeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output TypeI2COutput12 bAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort Size-Port StyleNo PortFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-LeadSupplier Device Package8-SMD		
CategorySensors, TransducersPressure Sensors, TransducersPackage8-SMD, J-LeadSeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output Type12COutput12 bAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort Size-Port StyleNo PortFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-LeadSupplier Device Package8-SMD	Manufacturer Part Number	HSCMNNN015PA2A5
Package 8-SMD, J-Lead Series TruStability? HSC Pressure Type Absolute Operating Pressure 15 PSI (103.42 kPa) Output Type 12C Output 12 b Accuracy ±0.25% Voltage - Supply 4.75 V ~ 5.25 V Port Size - Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
Package         8-SMD, J-Lead           Series         TruStability? HSC           Pressure Type         Absolute           Operating Pressure         15 PSI (103.42 kPa)           Output Type         I2C           Output         12 b           Accuracy         ±0.25%           Voltage - Supply         4.75 V ~ 5.25 V           Port Size         -           Port Style         No Port           Features         Amplified Output, Temperature Compensated           Termination Style         Surface Mount           Maximum Pressure         30 PSI (206.84 kPa)           Operating Temperature         -20°C ~ 85°C           Package / Case         8-SMD, J-Lead           Supplier Device Package         8-SMD	Category	Sensors, Transducers
SeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output Type12 COutput12 bAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort Size-Port StyleNo PortFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-LeadSupplier Device Package8-SMD		Pressure Sensors, Transducers
Pressure TypeAbsoluteOperating Pressure15 PSI (103.42 kPa)Output Type12COutput12 bAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort Size-Port StyleNo PortFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-LeadSupplier Device Package8-SMD	Package	8-SMD, J-Lead
Operating Pressure  15 PSI (103.42 kPa)  Output Type  12C  Output  12 b  Accuracy  4.75 V ~ 5.25 V  Port Size  - Port Style  No Port  Features  Amplified Output, Temperature Compensated  Termination Style  Surface Mount  Maximum Pressure  30 PSI (206.84 kPa)  Operating Temperature  -20°C ~ 85°C  Package / Case  Supplier Device Package  8-SMD	Series	TruStability? HSC
Output TypeI2COutput12 bAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort Size-Port StyleNo PortFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure30 PSI (206.84 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-LeadSupplier Device Package8-SMD	Pressure Type	Absolute
Output  Accuracy  ±0.25%  Voltage - Supply  4.75 V ~ 5.25 V  Port Size  - Port Style  No Port  Features  Amplified Output, Temperature Compensated  Termination Style  Surface Mount  Maximum Pressure  30 PSI (206.84 kPa)  Operating Temperature  -20°C ~ 85°C  Package / Case  8-SMD, J-Lead  Supplier Device Package  8-SMD	Operating Pressure	15 PSI (103.42 kPa)
Accuracy ±0.25%  Voltage - Supply 4.75 V ~ 5.25 V  Port Size -  Port Style No Port  Features Amplified Output, Temperature Compensated  Termination Style Surface Mount  Maximum Pressure 30 PSI (206.84 kPa)  Operating Temperature -20°C ~ 85°C  Package / Case 8-SMD, J-Lead  Supplier Device Package 8-SMD	Output Type	12C
Voltage - Supply  4.75 V ~ 5.25 V  Port Size  - Port Style  No Port  Features  Amplified Output, Temperature Compensated  Termination Style  Surface Mount  Maximum Pressure  30 PSI (206.84 kPa)  Operating Temperature  -20°C ~ 85°C  Package / Case  8-SMD, J-Lead  Supplier Device Package	Output	12 b
Port Size - No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 30 PSI (206.84 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Accuracy	±0.25%
Port Style No Port Features Amplified Output, Temperature Compensated  Termination Style Surface Mount  Maximum Pressure 30 PSI (206.84 kPa)  Operating Temperature -20°C ~ 85°C  Package / Case 8-SMD, J-Lead  Supplier Device Package 8-SMD	Voltage - Supply	4.75 V ~ 5.25 V
Features Amplified Output, Temperature Compensated  Termination Style Surface Mount  Maximum Pressure 30 PSI (206.84 kPa)  Operating Temperature -20°C ~ 85°C  Package / Case 8-SMD, J-Lead  Supplier Device Package 8-SMD	Port Size	-
Termination Style Surface Mount  Maximum Pressure 30 PSI (206.84 kPa)  Operating Temperature -20°C ~ 85°C  Package / Case 8-SMD, J-Lead  Supplier Device Package 8-SMD	Port Style	No Port
Maximum Pressure30 PSI (206.84 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-LeadSupplier Device Package8-SMD	Features	Amplified Output, Temperature Compensated
Operating Temperature -20°C ~ 85°C  Package / Case 8-SMD, J-Lead  Supplier Device Package 8-SMD	Termination Style	Surface Mount
Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Maximum Pressure	30 PSI (206.84 kPa)
Supplier Device Package 8-SMD	Operating Temperature	-20°C ~ 85°C
	Package / Case	8-SMD, J-Lead
Report errors?	Supplier Device Package	8-SMD
		Report errors?

#### **HSCMNNN015PA2A5** Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **HSCMNNN015PA2A5** Payment Methods



















## **HSCMNNN015PA2A5** Shipping Methods













If you have any question about HSCMNNN015PA2A5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com