

HSCMNNN1.6BAAA3

HSCMNNN1.6BAAA3 Information



For Reference Only

Part Number HSCMNNN1.6BAAA3

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description BRD MNT PRESSURE SENSORS

Package 8-SMD, J-Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HSCMNN1.6BAAA3 Specifications

Manufacturer Part Number HSCMNN1.6BAAA3 Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 8-SMD, J-Lead Series TruStability? HSC Pressure Type Absolute Operating Pressure 23.21 PSI (160 kPa) Output Type Analog Voltage Output 0.33 V ~ 2.97 V Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size - Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD		
CategorySensors, TransducersPackage8-SMD, J-LeadSeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure23.21 PSI (160 kPa)Output TypeAnalog VoltageOutput0.33 V ~ 2.97 VAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort Size-Port StyleNo PortFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure58.02 PSI (400 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-LeadSupplier Device Package8-SMD	Manufacturer Part Number	HSCMNNN1.6BAAA3
Package 8-SMD, J-Lead Series TruStability? HSC Pressure Type Absolute Operating Pressure Output Type Analog Voltage Output Output Quityut Quit	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 8-SMD, J-Lead Series TruStability? HSC Pressure Type Absolute Operating Pressure 23.21 PSI (160 kPa) Output Type Analog Voltage Output 0.33 V ~ 2.97 V Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size - Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Category	Sensors, Transducers
SeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure23.21 PSI (160 kPa)Output TypeAnalog VoltageOutput0.33 V ~ 2.97 VAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort Size-Port StyleNo PortFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure58.02 PSI (400 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-LeadSupplier Device Package8-SMD		Pressure Sensors, Transducers
Pressure Type Absolute Operating Pressure 23.21 PSI (160 kPa) Output Type Analog Voltage Output 0.33 V ~ 2.97 V Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size - Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Package	8-SMD, J-Lead
Operating Pressure 23.21 PSI (160 kPa) Output Type Analog Voltage Output 0.33 V ~ 2.97 V Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size - Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package	Series	TruStability? HSC
Output TypeAnalog VoltageOutput0.33 V ~ 2.97 VAccuracy±0.25%Voltage - Supply3 V ~ 3.6 VPort Size-Port StyleNo PortFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure58.02 PSI (400 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-LeadSupplier Device Package8-SMD	Pressure Type	Absolute
Output $0.33 \text{ V} \sim 2.97 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $3 \text{ V} \sim 3.6 \text{ V}$ Port Size-Port StyleNo PortFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure $58.02 \text{ PSI } (400 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 8-SMD , J-LeadSupplier Device Package 8-SMD	Operating Pressure	23.21 PSI (160 kPa)
Accuracy ±0.25% Voltage - Supply 3 V ~ 3.6 V Port Size - Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Output Type	Analog Voltage
Voltage - Supply 3 V ~ 3.6 V Port Size - Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Output	0.33 V ~ 2.97 V
Port Size - No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Accuracy	±0.25%
Port Style No Port Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Voltage - Supply	3 V ~ 3.6 V
Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Port Size	-
Termination Style Surface Mount Maximum Pressure 58.02 PSI (400 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Port Style	No Port
Maximum Pressure58.02 PSI (400 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-LeadSupplier Device Package8-SMD	Features	Amplified Output, Temperature Compensated
Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Termination Style	Surface Mount
Package / Case 8-SMD, J-Lead Supplier Device Package 8-SMD	Maximum Pressure	58.02 PSI (400 kPa)
Supplier Device Package 8-SMD	Operating Temperature	-20°C ~ 85°C
	Package / Case	8-SMD, J-Lead
Report errors?	Supplier Device Package	8-SMD
		Report errors?

HSCMNNN1.6BAAA3 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HSCMNN1.6BAAA3 Payment Methods



















HSCMNN1.6BAAA3 Shipping Methods













If you have any question about HSCMNN11.6BAAA3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com