

HSCMRRN030PAAA5

HSCMRRN030PAAA5 Information



For Reference Only

Part Number HSCMRRN030PAAA5

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

DescriptionSENSOR PRES 30PSI ABSO 5V SMT**Package**8-SMD, J-Lead, Dual Ports, Same Side

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HSCMRRN030PAAA5 Specifications

Manufacturer Part Number HSCMRRN030PAAA5 Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package 8-SMD, J-Lead, Dual Ports, Same Side Series TruStability? HSC Pressure Type Absolute Operating Pressure 30 PSI (206.84 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD		
CategorySensors, TransducersPackage8-SMD, J-Lead, Dual Ports, Same SideSeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure30 PSI (206.84 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 0.08" (1.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-Lead, Dual Ports, Same SideSupplier Device Package8-SMD	Manufacturer Part Number	HSCMRRN030PAAA5
Package 8-SMD, J-Lead, Dual Ports, Same Side Series TruStability? HSC Pressure Type Absolute Operating Pressure 30 PSI (206.84 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature - 20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
Package8-SMD, J-Lead, Dual Ports, Same SideSeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure30 PSI (206.84 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 0.08" (1.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-Lead, Dual Ports, Same SideSupplier Device Package8-SMD	Category	Sensors, Transducers
SeriesTruStability? HSCPressure TypeAbsoluteOperating Pressure30 PSI (206.84 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 0.08" (1.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure60 PSI (413.69 kPa)Operating Temperature-20°C ~ 85°CPackage / Case8-SMD, J-Lead, Dual Ports, Same SideSupplier Device Package8-SMD		Pressure Sensors, Transducers
Pressure Type 30 PSI (206.84 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Package	8-SMD, J-Lead, Dual Ports, Same Side
Operating Pressure 30 PSI (206.84 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package	Series	TruStability? HSC
Output TypeAnalog VoltageOutput $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Port SizeMale - 0.08 " (1.93mm) Tube, DualPort StyleBarbedFeaturesAmplified Output, Temperature CompensatedTermination StyleSurface MountMaximum Pressure $60 \text{ PSI (}413.69 \text{ kPa)}$ Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $8-\text{SMD}$, J-Lead, Dual Ports, Same SideSupplier Device Package $8-\text{SMD}$	Pressure Type	Absolute
Output $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Port Size $\text{Male} - 0.08'' (1.93\text{mm}) \text{ Tube}, \text{ Dual}$ Port Style Barbed Features $\text{Amplified Output, Temperature Compensated}$ Termination Style Surface Mount Maximum Pressure $60 \text{ PSI } (413.69 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case 8-SMD , J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Operating Pressure	30 PSI (206.84 kPa)
Accuracy ±0.25% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Output Type	Analog Voltage
Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Output	0.5 V ~ 4.5 V
Port Size Male - 0.08" (1.93mm) Tube, Dual Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Accuracy	±0.25%
Port Style Barbed Features Amplified Output, Temperature Compensated Termination Style Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Voltage - Supply	4.75 V ~ 5.25 V
Features Amplified Output, Temperature Compensated Surface Mount Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Port Size	Male - 0.08" (1.93mm) Tube, Dual
Termination Style Surface Mount 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Port Style	Barbed
Maximum Pressure 60 PSI (413.69 kPa) Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Features	Amplified Output, Temperature Compensated
Operating Temperature -20°C ~ 85°C Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Termination Style	Surface Mount
Package / Case 8-SMD, J-Lead, Dual Ports, Same Side Supplier Device Package 8-SMD	Maximum Pressure	60 PSI (413.69 kPa)
Supplier Device Package 8-SMD	Operating Temperature	-20°C ~ 85°C
	Package / Case	8-SMD, J-Lead, Dual Ports, Same Side
Report errors?	Supplier Device Package	8-SMD
		Report errors?

HSCMRRN030PAAA5 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HSCMRRN030PAAA5 Payment Methods

































If you have any question about HSCMRRN030PAAA5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com