

HSEC8-140-01-S-RA

HSEC8-140-01-S-RA Information

Heisener.com	Part Number Manufacturer Category Description Package	HSEC8-140-01-S-RA Samtec Inc. Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors 8MM HIGH SPEED DUAL R/A MO - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



HSEC8-140-01-S-RA Specifications

ManufacturerSamtec Inc.CategoryConnectors, Interconnects Card Edge Connectors - Edgeboard ConnectorsPackage-SeriesHSEC8-DVCard TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.031" (0.80mm)Features-Mounting TypeSurface Mount, Right AngleContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeGuldContact TypeGuldieverContact TypeBlack		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-SeriesHSEC8-DVCard TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions/Bay/Row0.062" (1.57mm)Number of Rows0.062" (1.57mm)Number of Rows2Pitch0.031" (0.80mm)Features-Nounting TypeSuface Mount, Right AngleContact MaterialGoldContact Finish ThicknessGoldContact TypeGuil (0.76µm)Contact TypeCantileverContact TypeBlackFaquere-ColorBlackFaquere-Starge Feature-Starge Feature-	Manufacturer Part Number	HSEC8-140-01-S-RA
Card Edge Connectors - Edgeboard ConnectorsPackage-SeriesHSEC8-DVCard TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.031" (0.80mm)Features-Mounting TypeSurface Mount, Right AngleContact MaterialGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Manufacturer	Samtec Inc.
Package-SeriesHSEC8-DVCard TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.031" (0.80mm)Features-Mounting TypeSurface Mount, Right AngleContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects
Series HSEC8-DV Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 40 Number of Positions 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.031" (0.80mm) Features - Mounting Type Surface Mount, Right Angle Contact Material Beryllium Copper Contact Finish Thickness Gold Contact Type Cantilever Color Black Flange Feature - Operating Temperature -		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.031" (0.80mm)Features-Mounting TypeSurface Mount, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeSurface Mount, CapterContact Finish ThicknessSolderContact TypeGoldContact TypeSurface Mount, CapterColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.031° (0.80mm)Features-Mounting TypeSolderContact MaterialSolderContact FinishGoldContact Finish ThicknessGoldContact TypeSoliderContact Finish ThicknessSoliderContact Finish	Series	HSEC8-DV
Number of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.031" (0.80mm)Features-Mounting TypeSulface Mount, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFange Feature-Operating Temperature-55°C~125°C	Card Type	Non Specified - Dual Edge
Number of Positions 80 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.031" (0.80mm) Features - Mounting Type Surface Mount, Right Angle Contact Material Solder Contact Finish Gold Contact Finish Thickness Gold Contact Type Cantilever Color Black Flange Feature - Operating Temperature -55°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.031" (0.80mm)Features-Mounting TypeSurface Mount, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Number of Positions/Bay/Row	40
Number of Rows2Pitch0.031" (0.80mm)Features-Mounting TypeSurface Mount, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Number of Positions	80
Pitch0.031" (0.80mm)Features-Mounting TypeSurface Mount, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeSurface Mount, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Number of Rows	2
Mounting TypeSurface Mount, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Pitch	0.031" (0.80mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Mounting Type	Surface Mount, Right Angle
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Contact Material	Beryllium Copper
Contact TypeCantileverColorBlackFlange Feature-Operating Temperature-55°C ~ 125°C	Contact Finish	Gold
Color Black Flange Feature - Operating Temperature -55°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange Feature-Operating Temperature-55°C ~ 125°C	Contact Type	Cantilever
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Color	Black
	Flange Feature	-
Report errors?	Operating Temperature	-55°C ~ 125°C
		Report errors?

HSEC8-140-01-S-RA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

HSEC8-140-01-S-RA Payment Methods



HSEC8-140-01-S-RA Shipping Methods



If you have any question about HSEC8-140-01-S-RA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com