



#### **HSMC-A460-U30M1 Information**

Heisener.com

Part NumberHSMC-A460-U30M1ManufacturerBroadcom LimitedCategoryOptoelectronics

LED Indication - Discrete

**Description** LED RED CLEAR 4PLCC SMD

Package 4-PLCC

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **HSMC-A460-U30M1 Specifications**

Manufacturer Part Number         HSMC-A460-U30M1           Manufacturer         Broadcom Limited           Category         Optoelectronics           LED Indication - Discrete           Package         4-PLCC           Series         -           Color         Red           Configuration         -           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         580mcd           Lens Style/Size         Round with Domed Top, 2.20mm           Voltage - Forward (Vf) (Typ)         2.2V           Current - Test         50mA           Viewing Angle         50°           Mounting Type         Surface Mount           Wavelength - Dominant         626nm           Wavelength - Peak         635nm           Features         -           Package / Case         4-PLCC           Supplier Device Package         4-PLCC           Size / Dimension         3.20mm L x 2.80mm W           Height (Max)         3.87mm	*	
Category         Optoelectronics           LED Indication - Discrete           Package         4-PLCC           Series         -           Color         Red           Configuration         -           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         580mcd           Lens Style/Size         Round with Domed Top, 2.20mm           Voltage - Forward (Vf) (Typ)         2.2V           Current - Test         50mA           Viewing Angle         50°           Mounting Type         Surface Mount           Wavelength - Dominant         626nm           Wavelength - Peak         635nm           Features         -           Package / Case         4-PLCC           Supplier Device Package         4-PLCC           Size / Dimension         3.20mm L x 2.80mm W	Manufacturer Part Number	HSMC-A460-U30M1
Package         4-PLCC           Series         -           Color         Red           Configuration         -           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         580mcd           Lens Style/Size         Round with Domed Top, 2.20mm           Voltage - Forward (Vf) (Typ)         2.2V           Current - Test         50mA           Viewing Angle         50°           Mounting Type         Surface Mount           Wavelength - Dominant         626nm           Wavelength - Peak         635nm           Features         -           Package / Case         4-PLCC           Supplier Device Package         4-PLCC           Size / Dimension         3.20mm L x 2.80mm W	Manufacturer	Broadcom Limited
Package         4-PLCC           Series         -           Color         Red           Configuration         -           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         580mcd           Lens Style/Size         Round with Domed Top, 2.20mm           Voltage - Forward (Vf) (Typ)         2.2V           Current - Test         50mA           Viewing Angle         50°           Mounting Type         Surface Mount           Wavelength - Dominant         626nm           Wavelength - Peak         635nm           Features         -           Package / Case         4-PLCC           Supplier Device Package         4-PLCC           Size / Dimension         3.20mm L x 2.80mm W	Category	Optoelectronics
Series         -           Color         Red           Configuration         -           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         580mcd           Lens Style/Size         Round with Domed Top, 2.20mm           Voltage - Forward (Vf) (Typ)         2.2V           Current - Test         50mA           Viewing Angle         50°           Mounting Type         Surface Mount           Wavelength - Dominant         626nm           Wavelength - Peak         635nm           Features         -           Package / Case         4-PLCC           Supplier Device Package         4-PLCC           Size / Dimension         3.20mm L x 2.80mm W		LED Indication - Discrete
ColorRedConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating580mcdLens Style/SizeRound with Domed Top, 2.20mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test50mAViewing Angle50°Mounting TypeSurface MountWavelength - Dominant626nmWavelength - Peak635nmFeatures-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm W	Package	4-PLCC
Configuration Lens Color Colorless Lens Transparency Clear Millicandela Rating 580mcd Lens Style/Size Round with Domed Top, 2.20mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 50mA Viewing Angle Sov Mounting Type Surface Mount Wavelength - Dominant Wavelength - Peak 635nm Features - Package / Case Supplier Device Package 4-PLCC Size / Dimension  Clear Colorless Lens Colorless Ander Colorles Ander Colorless Ander Colorles Ande	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating580mcdLens Style/SizeRound with Domed Top, 2.20mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test50mAViewing Angle50°Mounting TypeSurface MountWavelength - Dominant626nmWavelength - Peak635nmFeatures-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm W	Color	Red
Lens TransparencyClearMillicandela Rating580mcdLens Style/SizeRound with Domed Top, 2.20mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test50mAViewing Angle50°Mounting TypeSurface MountWavelength - Dominant626nmWavelength - Peak635nmFeatures-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm W	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 2.20mm Voltage - Forward (Vf) (Typ) 2.2V Current - Test 50mA Viewing Angle 50° Mounting Type Surface Mount Wavelength - Dominant 626nm Wavelength - Peak 635nm Features - Package / Case 4-PLCC Supplier Device Package Size / Dimension 580mcd Round with Domed Top, 2.20mm 620mm 620m 630mA 630mA 640m 640mm	Lens Color	Colorless
Lens Style/SizeRound with Domed Top, 2.20mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test50mAViewing Angle50°Mounting TypeSurface MountWavelength - Dominant626nmWavelength - Peak635nmFeatures-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm W	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ)  Current - Test  50mA  Viewing Angle  50°  Mounting Type  Surface Mount  Wavelength - Dominant  626nm  Wavelength - Peak  635nm  Features  - Package / Case  4-PLCC  Supplier Device Package  50°  4-PLCC  Size / Dimension  3.20mm L x 2.80mm W	Millicandela Rating	580mcd
Current - Test 50mA  Viewing Angle 50°  Mounting Type Surface Mount  Wavelength - Dominant 626nm  Wavelength - Peak 635nm  Features -  Package / Case 4-PLCC  Supplier Device Package 4-PLCC  Size / Dimension 3.20mm L x 2.80mm W	Lens Style/Size	Round with Domed Top, 2.20mm
Viewing Angle50°Mounting TypeSurface MountWavelength - Dominant626nmWavelength - Peak635nmFeatures-Package / Case4-PLCCSupplier Device Package4-PLCCSize / Dimension3.20mm L x 2.80mm W	Voltage - Forward (Vf) (Typ)	2.2V
Mounting Type Surface Mount  Wavelength - Dominant 626nm  Wavelength - Peak 635nm  Features - Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W	Current - Test	50mA
Wavelength - Dominant  Wavelength - Peak  635nm  Features  - Package / Case  4-PLCC  Supplier Device Package  4-PLCC  Size / Dimension  3.20mm L x 2.80mm W	Viewing Angle	50°
Wavelength - Peak 635nm  Features - Package / Case 4-PLCC  Supplier Device Package 4-PLCC  Size / Dimension 3.20mm L x 2.80mm W	Mounting Type	Surface Mount
Features - Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W	Wavelength - Dominant	626nm
Package / Case 4-PLCC Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W	Wavelength - Peak	635nm
Supplier Device Package 4-PLCC Size / Dimension 3.20mm L x 2.80mm W	Features	-
Size / Dimension 3.20mm L x 2.80mm W	Package / Case	4-PLCC
	Supplier Device Package	4-PLCC
Height (Max) 3.87mm	Size / Dimension	3.20mm L x 2.80mm W
	Height (Max)	3.87mm
Report errors?		Report errors?

#### HSMC-A460-U30M1 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **HSMC-A460-U30M1 Payment Methods**



















# **HSMC-A460-U30M1 Shipping Methods**













If you have any question about HSMC-A460-U30M1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com