

HSSR-7112-100 Information

Heisener.com

Part Number HSSR-7112-100

Manufacturer Broadcom Limited

Category Isolators

Special Purpose

Description OPTOISO 1.5KV POWER MOSFET 8SMD

Package 8-SMD Butt Joint

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HSSR-7112-100 Specifications

Manufacturer Part Number HSSR-7112-100 Manufacturer Broadcom Limited Category Isolators Package 8-SMD Butt Joint Series - Type Power MOSFET Number of Channels 1 Voltage - Isolation 1500VDC Common Mode Transient Immunity (Min) - Input Type DC Current - Output / Channel 1.6A Propagation Delay tpLH / tpHL (Max) 6ms, 0.25ms Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) 1.24V Current - DC Forward (If) (Max) 20mA Voltage - Supply - Operating Temperature -55°C ~ 125°C Mounting Type surface Mount Package / Case 8-SMD Butt Joint Supplier Device Package 8-SMD Butt Joint Approvals -		
Category Isolators Package 8-SMD Butt Joint Series - Type Power MOSFET Number of Channels 1 Voltage - Isolation 1500VDC Common Mode Transient Immunity (Min) - Input Type DC Current - Output / Channel 1.6A Propagation Delay tpLH / tpHL (Max) 6ms, 0.25ms Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) 1.24V Current - DC Forward (If) (Max) 20mA Voltage - Supply - Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SMD Butt Joint Supplier Device Package 8-SMD Butt Joint Approvals -	Manufacturer Part Number	HSSR-7112-100
Package 8-SMD Butt Joint Series - Type Power MOSFET Number of Channels 1 Voltage - Isolation 1500VDC Common Mode Transient Immunity (Min) - Input Type DC Current - Output / Channel 1.6A Propagation Delay tpLH / tpHL (Max) 6ms, 0.25ms Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) 1.24V Current - DC Forward (If) (Max) 20mA Voltage - Supply - Operating Temperature 55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SMD Butt Joint Supplier Device Package 8-SMD Butt Joint Approvals -	Manufacturer	Broadcom Limited
Package 8-SMD Butt Joint Series - Type Power MOSFET Number of Channels 1 Voltage - Isolation 1500VDC Common Mode Transient Immunity (Min) - Input Type DC Current - Output / Channel 1.6A Propagation Delay tpLH / tpHL (Max) 6ms, 0.25ms Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) 1.24V Current - DC Forward (If) (Max) 20mA Voltage - Supply - Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SMD Butt Joint Supplier Device Package 8-SMD Butt Joint Approvals -	Category	Isolators
Series - Type Power MOSFET Number of Channels 1 Voltage - Isolation 1500VDC Common Mode Transient Immunity (Min) - Input Type DC Current - Output / Channel 1.6A Propagation Delay tpLH / tpHL (Max) 6ms, 0.25ms Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) 1.24V Current - DC Forward (If) (Max) 20mA Voltage - Supply - Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SMD Butt Joint Supplier Device Package 8-SMD Butt Joint Approvals -		Special Purpose
TypePower MOSFETNumber of Channels1Voltage - Isolation1500VDCCommon Mode Transient Immunity (Min)-Input TypeDCCurrent - Output / Channel1.6APropagation Delay tpLH / tpHL (Max)6ms, 0.25msRise / Fall Time (Typ)-Voltage - Forward (Vf) (Typ)1.24VCurrent - DC Forward (If) (Max)20mAVoltage - Supply-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case8-SMD Butt JointSupplier Device Package8-SMD Butt JointApprovals-	Package	8-SMD Butt Joint
Number of Channels Voltage - Isolation Common Mode Transient Immunity (Min) Input Type DC Current - Output / Channel Propagation Delay tpLH / tpHL (Max) Rise / Fall Time (Typ) Voltage - Forward (Vf) (Typ) 1.24V Current - DC Forward (If) (Max) Voltage - Supply Operating Temperature Operating Type Surface Mount Package / Case Supplier Device Package Approvals Approvals	Series	-
Voltage - Isolation1500VDCCommon Mode Transient Immunity (Min)-Input TypeDCCurrent - Output / Channel1.6APropagation Delay tpLH / tpHL (Max)6ms, 0.25msRise / Fall Time (Typ)-Voltage - Forward (Vf) (Typ)1.24VCurrent - DC Forward (If) (Max)20mAVoltage - Supply-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case8-SMD Butt JointSupplier Device Package8-SMD Butt JointApprovals-	Туре	Power MOSFET
Common Mode Transient Immunity (Min) Input Type Current - Output / Channel 1.6A Propagation Delay tpLH / tpHL (Max) Rise / Fall Time (Typ) Voltage - Forward (Vf) (Typ) 1.24V Current - DC Forward (If) (Max) Voltage - Supply Operating Temperature Operating Type Surface Mount Package / Case 8-SMD Butt Joint Approvals - DC DC DC DC DC DC DC DC DC	Number of Channels	1
Input Type Current - Output / Channel 1.6A Propagation Delay tpLH / tpHL (Max) Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) 1.24V Current - DC Forward (If) (Max) Voltage - Supply - Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SMD Butt Joint Supplier Device Package Approvals - Current - OC	Voltage - Isolation	1500VDC
Current - Output / Channel 1.6A Propagation Delay tpLH / tpHL (Max) 6ms, 0.25ms Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) 1.24V Current - DC Forward (If) (Max) 20mA Voltage - Supply - Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SMD Butt Joint Supplier Device Package 8-SMD Butt Joint Approvals -	Common Mode Transient Immunity (Min)	-
Propagation Delay tpLH / tpHL (Max) Rise / Fall Time (Typ) Voltage - Forward (Vf) (Typ) 1.24V Current - DC Forward (If) (Max) Voltage - Supply Operating Temperature Mounting Type Surface Mount Package / Case Supplier Device Package Approvals 6ms, 0.25ms 6ms, 0.25ms	Input Type	DC
Rise / Fall Time (Typ) - Voltage - Forward (Vf) (Typ) 1.24V Current - DC Forward (If) (Max) 20mA Voltage - Supply - Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SMD Butt Joint Supplier Device Package 8-SMD Butt Joint Approvals - Operating Temperature -	Current - Output / Channel	1.6A
Voltage - Forward (Vf) (Typ) Current - DC Forward (If) (Max) Voltage - Supply Operating Temperature Operating Type Mounting Type Surface Mount Package / Case 8-SMD Butt Joint Approvals	Propagation Delay tpLH / tpHL (Max)	6ms, 0.25ms
Current - DC Forward (If) (Max) Voltage - Supply Operating Temperature -55°C ~ 125°C Mounting Type Surface Mount Package / Case 8-SMD Butt Joint Supplier Device Package Approvals -	Rise / Fall Time (Typ)	-
Voltage - Supply-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case8-SMD Butt JointSupplier Device Package8-SMD Butt JointApprovals-	Voltage - Forward (Vf) (Typ)	1.24V
Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case8-SMD Butt JointSupplier Device Package8-SMD Butt JointApprovals-	Current - DC Forward (If) (Max)	20mA
Mounting Type Surface Mount Package / Case 8-SMD Butt Joint Supplier Device Package 8-SMD Butt Joint Approvals -	Voltage - Supply	-
Package / Case 8-SMD Butt Joint Supplier Device Package 8-SMD Butt Joint Approvals -	Operating Temperature	-55°C ~ 125°C
Supplier Device Package 8-SMD Butt Joint Approvals -	Mounting Type	Surface Mount
Approvals -	Package / Case	8-SMD Butt Joint
	Supplier Device Package	8-SMD Butt Joint
Report errors?	Approvals	-
		Report errors?

HSSR-7112-100 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HSSR-7112-100 Payment Methods



















HSSR-7112-100 Shipping Methods













If you have any question about HSSR-7112-100, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com