



#### HV3102R24-22S01 Information

Heisener.com

Part Number HV3102R24-22S01 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** ER 4C 4#8 SKT RCPT BOX

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## HV3102R24-22S01 Specifications

Manufacturer Part Number     HV3102R24-22S01       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Circular Connectors       Package     -       Series     HV       Connector Type     Receptacle, Female Sockets       Number of Positions     4       Shell Size - Insert     24-22       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Crimp       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum Alloy, Olive Drab Cadmium Plated       Contact Finish     Silver       Features     -       Voltage - Rated     3500VAC, 5000VDC       Current Rating     7.5A		
CategoryConnectors, InterconnectsPackage-SeriesHVConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated3500VAC, 5000VDCCurrent Rating7.5A	Manufacturer Part Number	HV3102R24-22S01
Circular Connectors  Package - Series HV  Connector Type Receptacle, Female Sockets  Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 3500VAC, 5000VDC Current Rating 7.5A	Manufacturer	ITT Cannon, LLC
Package - HV Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 3500VAC, 5000VDC Current Rating 7.5A	Category	Connectors, Interconnects
SeriesHVConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated3500VAC, 5000VDCCurrent Rating7.5A		Circular Connectors
Connector Type Receptacle, Female Sockets  Number of Positions 4  Shell Size - Insert 24-22  Shell Size, MIL -  Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 3500VAC, 5000VDC  Current Rating 7.5A	Package	-
Number of Positions  Shell Size - Insert  24-22  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Voltage - Rated  3500VAC, 5000VDC  Current Rating  7.5A	Series	HV
Shell Size - Insert Shell Size, MIL	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Features - Voltage - Rated 3500VAC, 5000VDC Current Rating 7.5A	Number of Positions	4
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated3500VAC, 5000VDCCurrent Rating7.5A	Shell Size - Insert	24-22
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 3500VAC, 5000VDC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  -  Voltage - Rated  3500VAC, 5000VDC  Current Rating  7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 3500VAC, 5000VDC Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 3500VAC, 5000VDC  Current Rating 7.5A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  -  Voltage - Rated  7.5A	Orientation	N (Normal)
Contact Finish  Features  Voltage - Rated  Current Rating  Silver  -  7.5A	Ingress Protection	Environment Resistant
Features - Voltage - Rated 3500VAC, 5000VDC Current Rating 7.5A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 3500VAC, 5000VDC Current Rating 7.5A	Contact Finish	Silver
Current Rating 7.5A	Features	-
-	Voltage - Rated	3500VAC, 5000VDC
Report errors?	Current Rating	7.5A
		Report errors?

#### HV3102R24-22S01 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# HV3102R24-22S01 Payment Methods



















### HV3102R24-22S01 Shipping Methods













If you have any question about HV3102R24-22S01, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com