

HVA-3/8 Information

whelsene con

Part Number HVA-3/8 **Manufacturer** Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 375MA 1KVAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HVA-3/8 Specifications

Manufacturer Part NumberHVA-3/8ManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesHVFuse TypeCartridgeCurrent Rating375mAVoltage Rating - AC1000V (1kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.410" Dia x 2.996" L (10.41mm x 76.10mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesHVFuse TypeCartridgeCurrent Rating375mAVoltage Rating - AC1000V (1kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.410" Dia x 2.996" L (10.41mm x 76.10mm)	Manufacturer Part Number	HVA-3/8
Flectrical, Specialty Fuses Package Cartridge, Non-Standard Series HV Fuse Type Cartridge Current Rating 375mA Voltage Rating - AC 1000V (1kV) Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 2.996" L (10.41mm x 76.10mm)	Manufacturer	Eaton
Package Cartridge, Non-Standard Series HV Fuse Type Cartridge Current Rating 375mA Voltage Rating - AC 1000V (1kV) Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 2.996" L (10.41mm x 76.10mm)	Category	Circuit Protection
SeriesHVFuse TypeCartridgeCurrent Rating375mAVoltage Rating - AC1000V (1kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.410" Dia x 2.996" L (10.41mm x 76.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating375mAVoltage Rating - AC1000V (1kV)Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.410" Dia x 2.996" L (10.41mm x 76.10mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 1000V (1kV) Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 375mA 1000V (1kV) -	Series	HV
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 1000V (1kV) - 1000V (1kV)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Cartridge, Non-Standard O,410" Dia x 2.996" L (10.41mm x 76.10mm)	Current Rating	375mA
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial - Cless - Class - Cartridge, Non-Standard O.410" Dia x 2.996" L (10.41mm x 76.10mm)	Voltage Rating - AC	1000V (1kV)
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 2.996" L (10.41mm x 76.10mm)	Voltage Rating - DC	-
Features - Class - Case - Case Case Cartridge, Non-Standard Size / Dimension - O.410" Dia x 2.996" L (10.41mm x 76.10mm)	Response Time	Fast
Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage - Holder Package / Case Cartridge, Non-Standard Size / Dimension - O.410" Dia x 2.996" L (10.41mm x 76.10mm)	Applications	Electrical, Industrial
Approvals - Operating Temperature - Streaking Capacity @ Rated Voltage - Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 2.996" L (10.41mm x 76.10mm)	Features	-
Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 2.996" L (10.41mm x 76.10mm)	Class	-
Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 2.996" L (10.41mm x 76.10mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 2.996" L (10.41mm x 76.10mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.410" Dia x 2.996" L (10.41mm x 76.10mm)	Breaking Capacity @ Rated Voltage	-
Size / Dimension 0.410" Dia x 2.996" L (10.41mm x 76.10mm)	Mounting Type	Holder
` '	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.410" Dia x 2.996" L (10.41mm x 76.10mm)
		Report errors?

HVA-3/8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HVA-3/8 Payment Methods





















HVA-3/8 Shipping Methods













If you have any question about HVA-3/8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com