



HVR30D1M0K Information

Heisener.com

Part Number HVR30D1M0K

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 1M OHM 10% 50W

Package Axial, Tubular

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HVR30D1M0K Specifications

Manufacturer Part NumberHVR30D1M0KManufacturerTE Connectivity Passive ProductCategoryResistorsPackageAxial, TubularSeriesHVR, CGSResistance1 MOhmsTolerance±10%Power (Watts)50WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension1.181" Dia x 5.512" L (30.00mm x 140.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate-Report errors?	•	
CategoryResistorsPackageAxial, TubularSeriesHVR, CGSResistance1 MOhmsTolerance±10%Power (Watts)50WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension1.181" Dia x 5.512" L (30.00mm x 140.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate-	Manufacturer Part Number	HVR30D1M0K
PackageAxial, TubularSeriesHVR, CGSResistance1 MOhmsTolerance±10%Power (Watts)50WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension1.181" Dia x 5.512" L (30.00mm x 140.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate-	Manufacturer	TE Connectivity Passive Product
PackageAxial, TubularSeriesHVR, CGSResistance1 MOhmsTolerance±10%Power (Watts)50WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension1.181" Dia x 5.512" L (30.00mm x 140.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate-	Category	Resistors
SeriesHVR, CGSResistance1 MOhmsTolerance±10%Power (Watts)50WCompositionThick FilmTemperature Coefficient±300ppm/°COperating Temperature-FeaturesHigh Voltage, RF, High FrequencyCoating, Housing TypeAluminumMounting FeatureBrackets (not included)Size / Dimension1.181" Dia x 5.512" L (30.00mm x 140.00mm)Height - Seated (Max)-Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate-		Chassis Mount Resistors
Resistance 1 MOhms Tolerance ±10% Power (Watts) 50W Composition Thick Film Temperature Coefficient ±300ppm/°C Operating Temperature - Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 1.181" Dia x 5.512" L (30.00mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Package	Axial, Tubular
Tolerance ±10% Power (Watts) 50W Composition Thick Film Temperature Coefficient ±300ppm/°C Operating Temperature - Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 1.181" Dia x 5.512" L (30.00mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Series	HVR, CGS
Power (Watts) Composition Thick Film Temperature Coefficient ±300ppm/°C Operating Temperature - Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 1.181" Dia x 5.512" L (30.00mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Resistance	1 MOhms
Composition Thick Film Temperature Coefficient ±300ppm/°C Operating Temperature - Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 1.181" Dia x 5.512" L (30.00mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Tolerance	±10%
Temperature Coefficient ±300ppm/°C Operating Temperature - Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 1.181" Dia x 5.512" L (30.00mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Power (Watts)	50W
Operating Temperature Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 1.181" Dia x 5.512" L (30.00mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Composition	Thick Film
Features High Voltage, RF, High Frequency Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 1.181" Dia x 5.512" L (30.00mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Temperature Coefficient	±300ppm/°C
Coating, Housing Type Aluminum Mounting Feature Brackets (not included) Size / Dimension 1.181" Dia x 5.512" L (30.00mm x 140.00mm) Height - Seated (Max) Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Operating Temperature	-
Mounting Feature Brackets (not included) Size / Dimension 1.181" Dia x 5.512" L (30.00mm x 140.00mm) Height - Seated (Max) Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Features	High Voltage, RF, High Frequency
Size / Dimension 1.181" Dia x 5.512" L (30.00mm x 140.00mm) Height - Seated (Max) - Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Ferrule Ends (Ferrule Ends, M5 Thread) Package / Case Axial, Tubular Failure Rate -	Mounting Feature	Brackets (not included)
Lead StyleFerrule Ends (Ferrule Ends, M5 Thread)Package / CaseAxial, TubularFailure Rate-	Size / Dimension	1.181" Dia x 5.512" L (30.00mm x 140.00mm)
Package / Case Axial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Ferrule Ends (Ferrule Ends, M5 Thread)
	Package / Case	Axial, Tubular
Report errors?	Failure Rate	-
		Report errors?

HVR30D1M0K Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HVR30D1M0K Payment Methods



















HVR30D1M0K Shipping Methods













If you have any question about HVR30D1M0K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com