



HWB015S-05-M-C Information

For Reference Only

Part Number HWB015S-05-M-C

Manufacturer Sanken

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5V 15W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HWB015S-05-M-C Specifications

Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series HWB Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature -10°C ~ 60°C			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series HWB Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Manufacturer Part Number	HWB015S-05-M-C	
AC DC Converters Package - Series HWB Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Manufacturer	Sanken	
Package - Series HWB Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series HWB Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)		AC DC Converters	
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Package	-	
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Series	HWB	
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Туре	Enclosed	
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications ITE (Commercial), Medical Voltage - Isolation Voltage - Isolation - Efficiency Operating Temperature Features Load Sharing, Universal Input Mounting Type Size / Dimension 5V Applications 5V Applications - Chassis Mount Size / Dimension 5V Applications Chassis Mount Applications Chassis Mount Applications Applications Chassis Mount Applications Applications Applications Applications Applications Applications Chassis Mount Applications Applica	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency Operating Temperature Features Load Sharing, Universal Input Mounting Type Size / Dimension - - - - - - - - - - - - -	Voltage - Input	85 ~ 264 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency Operating Temperature Features Load Sharing, Universal Input Mounting Type Size / Dimension - Carrent - Output (Max) - ABA - A	Voltage - Output 1	5V	
Voltage - Output 4 Current - Output (Max) Apower (Watts) Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) - 15W Applications - 17E (Commercial), Medical - 70% Commercial), Medical - 10°C ~ 60°C Load Sharing, Universal Input Chassis Mount 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Voltage - Output 2	-	
Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 3A 15W Applications - Commercial), Medical - Load Sharing, Medical - Chassis Mount 10°C ~ 60°C Load Sharing, Universal Input Chassis Mount 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 15W 15W 10 Commercial), Medical - Chassis Mount 10°C ~ 60°C Load Sharing, Universal Input Chassis Mount 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Voltage - Output 4	-	
Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 70% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Current - Output (Max)	3A	
Voltage - Isolation Efficiency 70% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Power (Watts)	15W	
Efficiency 70% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Applications	ITE (Commercial), Medical	
Operating Temperature -10°C ~ 60°C Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Voltage - Isolation	-	
Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Efficiency	70%	
Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Operating Temperature	-10°C ~ 60°C	
Size / Dimension 4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	Features	Load Sharing, Universal Input	
, , , , , , , , , , , , , , , , , , ,	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	4.33" L x 3.62" W x 1.38" H (110.0mm x 92.0mm x 35.0mm)	
		Report erro	rs?

HWB015S-05-M-C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HWB015S-05-M-C Payment Methods



















HWB015S-05-M-C Shipping Methods













If you have any question about HWB015S-05-M-C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com