



HWB030D-15-M-C Information

For Reference Only

Part Number HWB030D-15-M-C

Manufacturer Sanken

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER +/-15V 30W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HWB030D-15-M-C Specifications

Manufacturer Part Number HWB030D-15-M-C Manufacturer Sanken Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series HWB Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series HWB Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Manufacturer Part Number	HWB030D-15-M-C	
Package - Series HWB Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Manufacturer	Sanken	
Package - Series HWB Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series HWB Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)		AC DC Converters	
Type Enclosed Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Package	-	
Number of Outputs 2 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Series	HWB	
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Туре	Enclosed	
Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Number of Outputs	2	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension -15V -0 -15V -15V -15V -15V -15V -15V -15V -15V	Voltage - Input	85 ~ 264 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial), Medical Voltage - Isolation Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension - Carrent - Output 4 - Carrent - Output (Max) - Commercial), Medical - Carrent - Output (Max) - Chassis Mount - Carrent - Output (Max) - Car	Voltage - Output 1	15V	
Voltage - Output 4 Current - Output (Max) 1.3A, 1.3A Power (Watts) 30W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension - 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Voltage - Output 2	-15V	
Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 1.3A, 1.3A 30W 1.3E (Commercial), Medical - Commercial), Medical - Size / Dimension - Size / Dimension 1.3A, 1.3A 1	Voltage - Output 3	-	
Power (Watts) 30W Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Voltage - Output 4	-	
Applications ITE (Commercial), Medical Voltage - Isolation - Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Current - Output (Max)	1.3A, 1.3A	
Voltage - Isolation Efficiency 80% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Power (Watts)	30W	
Efficiency 80% Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Applications	ITE (Commercial), Medical	
Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Voltage - Isolation	-	
Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Efficiency	80%	
Mounting Type Chassis Mount Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Operating Temperature	-10°C ~ 60°C	
Size / Dimension 5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	Features	Load Sharing, Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	5.35" L x 3.62" W x 1.38" H (136.0mm x 92.0mm x 35.0mm)	
			Report errors?

HWB030D-15-M-C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HWB030D-15-M-C Payment Methods



















HWB030D-15-M-C Shipping Methods













If you have any question about HWB030D-15-M-C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com