

# HWB030S-05

### HWB030S-05 Information

	Part Number Manufacturer Category Description Package	Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC CONVERTER 5V 30W - For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# HWB030S-05 Specifications

ManufacturerSankenCategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesHWBTypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Solation-Voltage - Isolation-Voltage - Isolation-Voltage - Solation-Voltage - Solation-	_			
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesHWBTypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)6AApplicationsITE (Commercial)Voltage - Isolation-Efficiency75%Operating TemperatureLoad Sharing, Universal Input	Manufacturer Part Number	HWB030S-05		
AC DC ConvertersPackage-SeriesHWBTypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)6APower (Watts)30WVoltage - Isolation-Efficiency75%Operating Temperature-Io°C ~ 60°CFeaturesLoad Sharing, Universal Input	Manufacturer	Sanken		
Package.SeriesHWBTypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 2.Voltage - Output 3.Voltage - Output 4.Voltage - Output 4.Voltage - Output 5.Voltage - Output 6.Voltage - Output 7.Voltage - Output 8.Voltage - Output 9.Voltage - Output 9.Voltage - Output 4.Power (Watts).Applications.Voltage - Isolation.Voltage - Isolation.Operating Temperature.Features.Voltage - Solation.Current - Output 4.Solations.Voltage - Isolation.Voltage - Isolation.Solations.Solati	Category	Power Supplies - External/Internal (Off-Board)		
NumberHWBTypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)6APower (Watts)30WApplications-Voltage - Isolation-Efficiency75%Operating Temperature-10°C ~ 60°CFeaturesLoad Sharing, Universal Input		AC DC Converters		
Type Open Frame   Number of Outputs 1   Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 5V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Voltage - Output 4 -   Current - Output (Max) 6A   Power (Watts) 30W   Applications -   Voltage - Isolation -   Efficiency 75%   Operating Temperature -   Features Load Sharing, Universal Input	Package	-		
Number of Outputs 1   Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 5V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 6A   Power (Watts) 30W   Voltage - Isolation -   Efficiency 75%   Operating Temperature -10°C ~ 60°C   Features Load Sharing, Universal Input	Series	HWB		
Voltage - Input 85 ~ 264 VAC   Voltage - Output 1 5V   Voltage - Output 2 -   Voltage - Output 3 -   Voltage - Output 4 -   Current - Output (Max) 6A   Power (Watts) 30W   Applications ITE (Commercial)   Voltage - Isolation -   Efficiency 75%   Operating Temperature -10°C ~ 60°C   Features Load Sharing, Universal Input	Туре	Open Frame		
Voltage - Output 15VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)6APower (Watts)30WApplicationsITE (Commercial)Voltage - Isolation-Efficiency75%Operating Temperature-10°C ~ 60°CFeaturesLoad Sharing, Universal Input	Number of Outputs	1		
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)6APower (Watts)30WApplicationsITE (Commercial)Voltage - Isolation-Efficiency75%Operating Temperature-10°C ~ 60°CFeaturesLoad Sharing, Universal Input	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)6APower (Watts)30WApplicationsITE (Commercial)Voltage - Isolation-Efficiency75%Operating Temperature-10°C ~ 60°CFeaturesLoad Sharing, Universal Input	Voltage - Output 1	5V		
Voltage - Output 4-Current - Output (Max)6APower (Watts)30WApplicationsITE (Commercial)Voltage - Isolation-Efficiency75%Operating Temperature-10°C ~ 60°CFeaturesLoad Sharing, Universal Input	Voltage - Output 2	-		
Current - Output (Max)6APower (Watts)30WApplicationsITE (Commercial)Voltage - Isolation-Efficiency75%Operating Temperature-10°C ~ 60°CFeaturesLoad Sharing, Universal Input	Voltage - Output 3	-		
Power (Watts)30WApplicationsITE (Commercial)Voltage - Isolation-Efficiency75%Operating Temperature-10°C ~ 60°CFeaturesLoad Sharing, Universal Input	Voltage - Output 4	-		
ApplicationsITE (Commercial)Voltage - Isolation-Efficiency75%Operating Temperature-10°C ~ 60°CFeaturesLoad Sharing, Universal Input	Current - Output (Max)	6A		
Voltage - Isolation-Efficiency75%Operating Temperature-10°C ~ 60°CFeaturesLoad Sharing, Universal Input	Power (Watts)	30W		
Efficiency75%Operating Temperature-10°C ~ 60°CFeaturesLoad Sharing, Universal Input	Applications	ITE (Commercial)		
Operating Temperature-10°C ~ 60°CFeaturesLoad Sharing, Universal Input	Voltage - Isolation	-		
Features Load Sharing, Universal Input	Efficiency	75%		
	Operating Temperature	$-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$		
	Features	Load Sharing, Universal Input		
Mounting Type Chassis Mount	Mounting Type	Chassis Mount		
Size / Dimension 5.35" L x 3.62" W x 1.34" H (136.0mm x 92.0mm x 34.0mm)	Size / Dimension	5.35" L x 3.62" W x 1.34" H (136.0mm x 92.0mm x 34.0mm)		
Report err		Report errors?		

#### HWB030S-05 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE SUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### HWB030S-05 Payment Methods



# HWB030S-05 Shipping Methods



If you have any question about HWB030S-05, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com