



## **HWB030S-12-M Information**

Heisener.com

Part Number HWB030S-12-M

Manufacturer Sanken

Category Power Supplies - External/Internal (Off-Board)

**AC DC Converters** 

**Description** AC/DC CONVERTER 12V 30W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **HWB030S-12-M Specifications**

Manufacturer         Sanken           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         HWB           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3A           Power (Watts)         30W           Applications         ITE (Commercial), Medical           Voltage - Isolation         -           Efficiency         77%           Operating Temperature         -10°C ~ 60°C           Features         Load Sharing, Universal Input		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         HWB           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3A           Applications         ITE (Commercial), Medical           Voltage - Isolation         -           Efficiency         77%           Operating Temperature         -10°C ~ 60°C           Features         Load Sharing, Universal Input	Manufacturer Part Number	HWB030S-12-M
AC DC Converters	Manufacturer	Sanken
Package         -           Series         HWB           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3A           Power (Watts)         30W           Applications         ITE (Commercial), Medical           Voltage - Isolation         -           Efficiency         77%           Operating Temperature         -10°C ~ 60°C           Features         Load Sharing, Universal Input	Category	Power Supplies - External/Internal (Off-Board)
Series         HWB           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3A           Power (Watts)         30W           Applications         ITE (Commercial), Medical           Voltage - Isolation         -           Efficiency         77%           Operating Temperature         -10°C ~ 60°C           Features         Load Sharing, Universal Input		AC DC Converters
Type Open Frame  Number of Outputs 1  Voltage - Input 85 ~ 264 VAC  Voltage - Output 1 12V  Voltage - Output 2 -  Voltage - Output 3 -  Voltage - Output 4 -  Current - Output (Max) 3A  Power (Watts) 30W  Applications ITE (Commercial), Medical  Voltage - Isolation -  Efficiency 77%  Operating Temperature -10°C ~ 60°C  Features Load Sharing, Universal Input	Package	-
Number of Outputs       1         Voltage - Input       85 ~ 264 VAC         Voltage - Output 1       12V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       3A         Power (Watts)       30W         Applications       ITE (Commercial), Medical         Voltage - Isolation       -         Efficiency       77%         Operating Temperature       -10°C ~ 60°C         Features       Load Sharing, Universal Input	Series	HWB
Voltage - Input  85 ~ 264 VAC  Voltage - Output 1  12V  Voltage - Output 2  - Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial), Medical  Voltage - Isolation  - Efficiency  Operating Temperature  Features  85 ~ 264 VAC  12V  NAC  12V  -  CUTOMIC Temperature  -  85 ~ 264 VAC  -  12V  12V	Type	Open Frame
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial), Medical  Voltage - Isolation  - Efficiency  Operating Temperature  - 10°C ~ 60°C  Features  I2V  -  -  -  -  -  -  -  -  -  -  -  -  -	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial), Medical  Voltage - Isolation  Efficiency  Operating Temperature  -10°C ~ 60°C  Features  - Load Sharing, Universal Input	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial), Medical  Voltage - Isolation  -  Efficiency  Operating Temperature  Features  - Output (Max)  - ADDED TO THE COMMERCIAL AND THE CO	Voltage - Output 1	12V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial), Medical  Voltage - Isolation  -  Efficiency  Operating Temperature  Features  - Output (Max)  - Temperature  - 10°C ~ 60°C  Load Sharing, Universal Input	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial), Medical  Voltage - Isolation  -  Efficiency  77%  Operating Temperature  -10°C ~ 60°C  Features  Load Sharing, Universal Input	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial), Medical  Voltage - Isolation	Voltage - Output 4	-
Applications ITE (Commercial), Medical  Voltage - Isolation -  Efficiency 77%  Operating Temperature -10°C ~ 60°C  Features Load Sharing, Universal Input	Current - Output (Max)	3A
Voltage - Isolation -  Efficiency 77%  Operating Temperature -10°C ~ 60°C  Features Load Sharing, Universal Input	Power (Watts)	30W
Efficiency 77%  Operating Temperature -10°C ~ 60°C  Features Load Sharing, Universal Input	Applications	ITE (Commercial), Medical
Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Features Load Sharing, Universal Input	Voltage - Isolation	-
Features Load Sharing, Universal Input	Efficiency	77%
	Operating Temperature	-10°C ~ 60°C
Mounting Type Chassis Mount	Features	Load Sharing, Universal Input
	Mounting Type	Chassis Mount
Size / Dimension 5.35" L x 3.62" W x 1.34" H (136.0mm x 92.0mm x 34.0mm)	Size / Dimension	5.35" L x 3.62" W x 1.34" H (136.0mm x 92.0mm x 34.0mm)
Report erro		Report errors?

#### **HWB030S-12-M Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **HWB030S-12-M Payment Methods**



















# **HWB030S-12-M Shipping Methods**













If you have any question about HWB030S-12-M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com