



HWB060S-05 Information



For Reference Only

Part Number HWB060S-05

Manufacturer Sanken

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5V 60W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TIMEDOCOS OF	Chacifications
H W BUOUS-US	Specifications

Manufacturer Part Number HWB060S-05 Manufacturer Sanken Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series HWB Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 75% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series HWB Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 75% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)	Manufacturer Part Number	HWB060S-05
Package - Series HWB Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 75% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)	Manufacturer	Sanken
Package - Series HWB Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 75% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series HWB Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 75% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 75% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 75% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)	Series	HWB
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 75% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)	Туре	Open Frame
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature Features Load Sharing, Universal Input Mounting Type Size / Dimension 5V - Current - Output (Max)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Voltage - Isolation - Efficiency Operating Temperature Features Load Sharing, Universal Input Mounting Type Size / Dimension - Control Output (Max) Current - Output (Max) Control Output (Max) Contr	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max)	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 75% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) 10A - 10B Commercial) - Commercial Comm	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 75% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 10A 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)	Voltage - Output 3	-
Power (Watts) 60W Applications ITE (Commercial) Voltage - Isolation - Efficiency 75% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation - Efficiency 75% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)	Current - Output (Max)	10A
Voltage - Isolation Efficiency 75% Operating Temperature -10°C ~ 60°C Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)	Power (Watts)	60W
Efficiency 75% Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ FeaturesLoad Sharing, Universal InputMounting TypeChassis MountSize / Dimension $6.69^{\circ}\text{L x } 3.62^{\circ}\text{W x } 1.50^{\circ}\text{H } (170.0\text{mm x } 92.0\text{mm x } 38.0\text{mm})$	Applications	ITE (Commercial)
Operating Temperature $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ FeaturesLoad Sharing, Universal InputMounting TypeChassis MountSize / Dimension 6.69 " L x 3.62 " W x 1.50 " H (170.0mm x 92.0mm x 38.0mm)	Voltage - Isolation	-
Features Load Sharing, Universal Input Mounting Type Chassis Mount Size / Dimension 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)	Efficiency	75%
Mounting Type Chassis Mount Size / Dimension 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)	Operating Temperature	-10°C ~ 60°C
Size / Dimension 6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)	Features	Load Sharing, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	6.69" L x 3.62" W x 1.50" H (170.0mm x 92.0mm x 38.0mm)
		Report errors?

HWB060S-05 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HWB060S-05 Payment Methods



















HWB060S-05 Shipping Methods













If you have any question about HWB060S-05, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com