

HWS15-24/A Information



For Reference Only

Part Number HWS15-24/A

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 15W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HWS15-24/A Specifications

Manufacturer Part Number HWS15-24/A Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series HWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 650mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)	-	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series HWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 650mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)	Manufacturer Part Number	HWS15-24/A
Package - Series HWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 650mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series HWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 650mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series HWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 650mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 650mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)	Package	-
Number of Outputs Voltage - Input 85 ~ 265 VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Sty (3000V) Efficiency 92% Operating Temperature -10°C ~ 70°C (With Derating) Features Mounting Type Chassis Mount Size / Dimension 1 Input Size / Dimension Size / Dimension 1 Input Size / Dimension Size / Dimension Size / Size / Dimension Size / Size / Dimension Size / Size / Dimension	Series	HWS
Voltage - Input85 ~ 265 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)650mAPower (Watts)15WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency82%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)	Type	Enclosed
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Size / Dimension 24V - Current - Output (Max)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Size / Dimension - Size / Dimension - Size / Dimension - Current - Output (Max)	Voltage - Input	85 ~ 265 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Sifficiency Operating Temperature Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - Output 4 - Output (Max) - Osoma -	Voltage - Output 1	24V
Voltage - Output 4 Current - Output (Max) 650mA Power (Watts) 15W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 650mA 650m 650mA 650m 65	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)	Voltage - Output 4	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Current - Output (Max)	650mA
Voltage - Isolation 3kV (3000V) Efficiency 82% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)	Power (Watts)	15W
Efficiency 82% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)	Applications	ITE (Commercial)
Operating Temperature -10°C ~ 70°C (With Derating) Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)	Efficiency	82%
Mounting Type Chassis Mount Size / Dimension 3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)	Operating Temperature	$-10^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)	Features	Adjustable Output, DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	3.15" L x 1.24" W x 3.23" H (80.0mm x 31.5mm x 82.0mm)
		Report errors?

HWS15-24/A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HWS15-24/A Payment Methods



















HWS15-24/A Shipping Methods













If you have any question about HWS15-24/A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com