

HWS30-15/A Information

Part Number HWS30-15/A

Manufacturer TDK-Lambda Americas Inc.

Power Supplies - External/Internal (Off-Board) Category

AC DC Converters

Description AC/DC CONVERTER 15V 30W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









HWS30-15/A Specifications

| Manufacturer Part Number HWS30-15/A Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series HWS Type Enclosed Number of Outputs 1 Voltage - Input 85 - 265 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3KV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | | |
|--|--------------------------|---|
| Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series HWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Manufacturer Part Number | HWS30-15/A |
| Package - Series HWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Manufacturer | TDK-Lambda Americas Inc. |
| Package - Series HWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Category | Power Supplies - External/Internal (Off-Board) |
| Series HWS Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | | AC DC Converters |
| Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Package | - |
| Number of Outputs 1 Voltage - Input 85 ~ 265 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2A Power (Watts) 30W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Series | HWS |
| Voltage - Input85 ~ 265 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2APower (Watts)30WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency83%Operating Temperature-10°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Universal InputMounting TypeChassis MountSize / Dimension3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Type | Enclosed |
| Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Size / Dimension 15V - Size / Dimension 15V - 15V 15V 15V 15V 15V - 10°C ~ 70°C (With Derating) The Chassis Mount Size / Dimension 15V - 10°C ~ 70°C (With Value of the Size of the | Number of Outputs | 1 |
| Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Voltage - Input | 85 ~ 265 VAC |
| Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Apower (Watts) Applications ITE (Commercial) Voltage - Isolation Size / Dimension Size / Dimension - Current - Output (Max) - Adjustable Output, DC Input Capable, Universal Input Size / Dimension - Current - Output (Max) - Chassis Mount - Chassis Mount | Voltage - Output 1 | 15V |
| Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Voltage - Output 2 | - |
| Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Voltage - Output 3 | - |
| Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Voltage - Output 4 | - |
| $ \begin{array}{llllllllllllllllllllllllllllllllllll$ | Current - Output (Max) | 2A |
| Voltage - Isolation 3kV (3000V) Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Power (Watts) | 30W |
| Efficiency 83% Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Applications | ITE (Commercial) |
| Operating Temperature -10°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Voltage - Isolation | 3kV (3000V) |
| Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Efficiency | 83% |
| Mounting Type Chassis Mount Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Operating Temperature | $-10^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating) |
| Size / Dimension 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) | Features | Adjustable Output, DC Input Capable, Universal Input |
| | Mounting Type | Chassis Mount |
| Report errors? | Size / Dimension | 3.74" L x 1.24" W x 3.23" H (95.0mm x 31.5mm x 82.0mm) |
| | | Report errors? |

HWS30-15/A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

HWS30-15/A Payment Methods



















HWS30-15/A Shipping Methods













If you have any question about HWS30-15/A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com