

ICC3SAD2100

ICC3SAD2100 Information

www.heisener.com	Part Number Manufacturer Category Description Package	Switches Pushbutton Switches SWITCH PUSH SPST-NO 5A 48V	
		For the pricing/inventory/lead time, please contact us	IIIIIIIIIIIIIII
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ICC3SAD2100 Specifications

Manufacturer APEM Inc. Category Switches Pushbutton Switches Pushbutton Switches Package - Series C Type Standard Circuit SPST-NO Switch Function Off-Mom Current Rating S00mA (AC), 5A (DC) Voltage Rating - AC Square, Button Voltage Rating - DC Square, Button Coro - Actuator/Cap Black Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Solder Lug Termination Style Solder Lug Fatures Foxy Scaled Terminals		
CategorySwitchesPackage-Package-SeriesICTypeStandardCircuitSPST-NOSwitch FunctionOff-MomCurrent Rating500mA (AC), 5A (DC)Voltage Rating - ACSaverVoltage Rating - DCSaverCoror - Actuator/CapBlackIllumination Type, Color-Illumination Voltage (Nominal)-Monting TypeSolder LugIngress ProtectionFor Just Tight, WaterproofFeaturesEyoy Sealed TerminalsPanel Cuotu DimensionsCircular - 13.60mm Dia	Manufacturer Part Number	ICC3SAD2100
Pushbutton SwitchesPackage-SeriesICTypeStandardCircuitSPST-NOSwitch FunctionOff-MomCurrent RatingS00mA (AC), 5A (DC)Voltage Rating - AC48VVoltage Rating - DCSquare, ButtonColor - Actuator/CapBlackIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugIngress ProtectionFory Scaled TerminalsFeaturesEpoxy Scaled TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Manufacturer	APEM Inc.
Package-SeriesICStradardStandardTypeStandardCircuitSPST-NOSwitch FunctionOff-MornCurrent RatingS00mA (AC), 5A (DC)Voltage Rating - AC48VVoltage Rating - DCSayare, ButtonColor - Actuator/CapBlackIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypeSolder LugIngress ProtectionForst Tight, WaterproofFaturesEpsy Sealed TerminalsPael Cutout DimensionsCircuar - 13.60mm Dia	Category	Switches
SeriesICTypeStandardTypeStandardCircuitSPST-NOSwitch FunctionOff-MomCurrent RatingS00mA (AC), 5A (DC)Voltage Rating - AC48VVoltage Rating - DCSquare, ButtonColor - Actuator/CapBlackIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugIngress ProtectionSolder LugFaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia		Pushbutton Switches
TypeStandardCircuitSPST-NOSwitch FunctionOff-MomCurrent Rating500mA (AC), 5A (DC)Voltage Rating - AC48VVoltage Rating - DC28VActuator TypeSquare, ButtonColor - Actuator/CapBlackIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugIngress ProtectionSolder LugIngress ProtectionFory Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Package	-
CircuitSPST-NOSwitch FunctionOff-MomCurrent Rating500mA (AC), 5A (DC)Voltage Rating - AC48VVoltage Rating - DC28VActuator TypeSquare, ButtonColor - Actuator/CapBlackIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Series	IC
Switch FunctionOff-MomCurrent Rating500mA (AC), 5A (DC)Voltage Rating - AC48VVoltage Rating - DC28VActuator TypeSquare, ButtonColor - Actuator/CapBlackIllumination Type, Color-Illumination Type, Color-Mounting TypeOdder LugTermination StyleSolder LugIngress ProtectionP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Туре	Standard
Current Rating500mA (AC), 5A (DC)Voltage Rating - AC48VVoltage Rating - DC28VActuator TypeSquare, ButtonColor - Actuator/CapBlackIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Circuit	SPST-NO
Voltage Rating - AC48VVoltage Rating - DC28VActuator TypeSquare, ButtonColor - Actuator/CapBlackIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionPfo7 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Switch Function	Off-Mom
Voltage Rating - DC28VActuator TypeSquare, ButtonColor - Actuator/CapBlackIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionProf - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Current Rating	500mA (AC), 5A (DC)
Actuator TypeSquare, ButtonColor - Actuator/CapBlackIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Voltage Rating - AC	48V
Color - Actuator/CapBlackIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Voltage Rating - DC	28V
Illumination Type, Color-Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Actuator Type	Square, Button
Illumination Voltage (Nominal)-Mounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Color - Actuator/Cap	Black
Mounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Illumination Type, Color	-
Termination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Illumination Voltage (Nominal)	-
Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Mounting Type	Panel Mount, Front
FeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Termination Style	Solder Lug
Panel Cutout Dimensions Circular - 13.60mm Dia	Ingress Protection	IP67 - Dust Tight, Waterproof
	Features	Epoxy Sealed Terminals
Report errors?	Panel Cutout Dimensions	Circular - 13.60mm Dia
		Report errors?

ICC3SAD2100 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ICC3SAD2100 Payment Methods



ICC3SAD2100 Shipping Methods



If you have any question about ICC3SAD2100, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com