

ICO-316-SST

ICO-316-SST Information

Heisener.com	Part Number Manufacturer Category Description Package	ICO-316-SST Samtec Inc. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 16POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ICO-316-SST Specifications

Manufacturer Part NumberICO-316-SSTManufacturerSamtec Inc.CategoryConnectors, InterconnectsSockets for ICs, TransistorsPackage-SeriesICOMumber of Positions or Pins (Grid)BP, 0.3" (7.62mm) Row SpacingPitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Material - MatingGoldMunting TypeBeryllium CopperMounting TypeOpen FrameFeaturesOpen FrameTerminationSolderPitch - PostGoldContact Finish - PostSolderContact Finish Thickness - PostSolderContact Finish - PostTinContact Finish - PostSolderContact Finish - PostSolderContact Finish - PostSolderContact Finish Thickness - PostSolderContact Finish Thickness - PostPinsContact Finish Thickness - PostSolderContact Finish Thickness - PostSolderContact Finish Thickness - PostSolderContact Finish Thickness - PostSolderContact Finish Thickness - PostPinsContact Finish Thickness - PostSolderContact Finish ThicknessSolderContact Finish Thickness <td< th=""><th></th><th></th></td<>		
CategoryConnectors, Interconnects sockets for ICs, TransistorsPackage-SeriesICOTypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBerylium CopperContact Material - MatingBerylium CopperFeaturesOpen FrameFreminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - PostSolderContact Finish Thickness - PostSolderFinish - PostTinContact Finish Thickness - Post-Contact Finish Thickness - PostSolderFinish - PostSolderContact Finish Thickness - PostSolderFinish Thickness - Post-Contact Finish Thickness - Post-Finish Thickness - Post-Contact Finish Thickness - Post-Solder-Finish Thickness - Post-Contact Finish Thickness - Post-Contact Finish Thickness - Post-Finish Thickness - Post-Contact Finish Thickness - Post-Contact Finish Thickness - Post-Contact Finish Thickness - Post-Finish Thickness - Post-Contact Finish Thickness - Post-Contact Finish Thickness - Post-Contact Finish Thickness - Post-Contact Fini	Manufacturer Part Number	ICO-316-SST
NumberSockets for ICs, TransistorsPackage-SeriesICOTypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - MatingOlo0" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperContact Material - MatingOpen FrameFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - PostSolderContact Finish Thickness - PostTinContact Finish Thickness - PostSenseHousing Material - PostBrassHousing MaterialSolges Filled	Manufacturer	Samtec Inc.
Package.SeriesICOTypeDIP,0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - MatingOl00" (2.54mm)Contact Finish - MatingGoldContact Finish - MatingIoµin (0.25µm)Contact Finish - MatingBeryllium CopperContact Material - MatingDen FrameFeaturesOpen FrameFreminationSolderPitch - PostIn10" (2.54mm)Contact Finish - PostSolderContact Finish - PostTinContact Finish - PostSolderHouse - PostSingenHouse - PostSingenContact Material - PostSingenHouse - PostSingenContact Material - PostSingenHouse - PostSingenContact Material - PostSingenHousing MaterialSingenHousing MaterialSingenContact Finish - PostSingenContact Material - PostSingenContact Finish - PostSingenContact - PostSingenContact - PostSingenContact - PostSingen <td>Category</td> <td>Connectors, Interconnects</td>	Category	Connectors, Interconnects
SeriesICOTypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating10µin (0.25µm)Contact Finish Thickness - MatingBeryllium CopperContact Material - MatingDen FrameFeaturesOpen FrameFreminationSolderPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish Thickness - PostTinContact Finish Thickness - PostSasHousing Material - PostParseContact Material - PostParseContact Material - PostParseContact Finish Thickness - PostParseContact Material - PostParseContact PostParse </td <td></td> <td>Sockets for ICs, Transistors</td>		Sockets for ICs, Transistors
TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post50 derContact Finish Thickness - Post-Contact Finish Thickness - Post-Housing Material - PostPoyester, Glass Filled	Package	-
Number of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostTinContact Finish Thickness - PostSolderHousing TypeSolderPostTinContact Finish Thickness - Post-PostSolder <td>Series</td> <td>ICO</td>	Series	ICO
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostTinContact Finish Thickness - PostSolderIcontact Finish Thickness - PostSaleHousing Material - MostPoyester, Glass Filled	Туре	DIP, 0.3" (7.62mm) Row Spacing
Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post-Contact Finish - PostSilenHouring Type-PostSolderContact Finish Thickness - PostFinsHousing MaterialPolyester, Glass Filled	Number of Positions or Pins (Grid)	16 (2 x 8)
Contact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass Filled	Pitch - Mating	0.100" (2.54mm)
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - PostSalarContact Finish - PostBrassHousing Material - Mating - Material	Contact Finish - Mating	Gold
Mounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass Filled	Contact Finish Thickness - Mating	10µin (0.25µm)
FeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass Filled	Contact Material - Mating	Beryllium Copper
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass Filled	Mounting Type	Through Hole
Pitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass Filled	Features	Open Frame
Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass Filled	Termination	Solder
Contact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass Filled	Pitch - Post	0.100" (2.54mm)
Contact Material - PostBrassHousing MaterialPolyester, Glass Filled	Contact Finish - Post	Tin
Housing Material Polyester, Glass Filled	Contact Finish Thickness - Post	-
-	Contact Material - Post	Brass
	Housing Material	Polyester, Glass Filled
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-55°C ~ 125°C
Report error		Report errors?

ICO-316-SST Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ICO-316-SST Payment Methods \swarrow WIRE ransfer PayPal wile payear PayPal wile payear PayPal wile payear wile paye

If you have any question about ICO-316-SST, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com