



## **ICO-640-ZLGT Information**

Heisener.com

Part Number ICO-640-ZLGT Manufacturer Samtec Inc.

Category Connectors, Interconnects

Sockets for ICs, Transistors

**Description** CONN IC DIP SOCKET 40POS GOLD

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com

Request a Quote



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ICO-640-ZLGT Specifications**

Manufacturer Part Number         ICO-640-ZLGT           Manufacturer         Samtee Inc.           Category         Connectors, Interconnects           Sockets for ICs, Transistors         Sockets for ICs, Transistors           Package         -           Series         ICO           Type         DIP, 0.6" (15.24mm) Row Spacing           Number of Positions or Pins (Grid)         40 (2 x 20)           Pitch - Mating         Gold           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         30µin (0.76µm)           Contact Material - Mating         Beryllium Copper           Mounting Type         Through Hole           Features         Open Frame           Termination         Solder           Pitch - Post         0.100" (2.54mm)           Contact Finish - Post         Tin           Contact Finish Thickness - Post         -           Contact Material - Post         Brass           Housing Material         Polyester, Glass Filled           Operating Temperature         -55°C ~ 125°C	*	
CategoryConnectors, InterconnectsSockets for ICs, TransistorsPackage-SeriesICOTypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass FilledOperating Temperature-55°C ~ 125°C	Manufacturer Part Number	ICO-640-ZLGT
Sockets for ICs, TransistorsPackage-SeriesICOTypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass FilledOperating Temperature-55°C ~ 125°C	Manufacturer	Samtec Inc.
Package-SeriesICOTypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - Post-Contact Finish Thickness - Post-Contact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass FilledOperating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects
SeriesICOTypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass FilledOperating Temperature-55°C ~ 125°C		Sockets for ICs, Transistors
TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass FilledOperating Temperature-55°C ~ 125°C	Package	-
Number of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass FilledOperating Temperature-55°C ~ 125°C	Series	ICO
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass FilledOperating Temperature-55°C ~ 125°C	Type	DIP, 0.6" (15.24mm) Row Spacing
Contact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass FilledOperating Temperature-55°C ~ 125°C	Number of Positions or Pins (Grid)	40 (2 x 20)
Contact Finish Thickness - Mating Contact Material - Mating Beryllium Copper Mounting Type Through Hole Features Open Frame Termination Solder Pitch - Post 0.100" (2.54mm)  Contact Finish - Post Tin Contact Finish Thickness - Post - Contact Material - Post Brass Housing Material Operating Temperature  30µin (0.76µm) Beryllium Copper  Through Hole Open Frame  Open Frame  - Copen Frame  Solder	Pitch - Mating	0.100" (2.54mm)
Contact Material - Mating  Mounting Type  Through Hole  Features  Open Frame  Termination  Solder  Pitch - Post  Contact Finish - Post  Tin  Contact Finish Thickness - Post  Contact Material - Post  Housing Material  Operating Temperature  Beryllium Copper  Through Hole  Open Frame  Open Frame  1.  Open Frame  Ontogen Frame  Open Frame  Folder  Open Frame  Open Fr	Contact Finish - Mating	Gold
Mounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolyester, Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	30μin (0.76μm)
Features Open Frame Termination Solder Pitch - Post 0.100" (2.54mm)  Contact Finish - Post Tin Contact Finish Thickness - Post - Contact Material - Post Brass Housing Material Operating Temperature Open Frame Open Frame Solder Open Frame Open Frame Open Frame Solder Open Frame Open Frame Solder Open Frame O	Contact Material - Mating	Beryllium Copper
Termination Solder  Pitch - Post 0.100" (2.54mm)  Contact Finish - Post Tin  Contact Finish Thickness - Post - Contact Material - Post Brass  Housing Material Polyester, Glass Filled  Operating Temperature -55°C ~ 125°C	Mounting Type	Through Hole
Pitch - Post 0.100" (2.54mm)  Contact Finish - Post Tin  Contact Finish Thickness - Post -  Contact Material - Post Brass  Housing Material Polyester, Glass Filled  Operating Temperature -55°C ~ 125°C	Features	Open Frame
Contact Finish - Post Contact Finish Thickness - Post - Contact Material - Post Brass Housing Material Polyester, Glass Filled Operating Temperature -55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Post  Contact Material - Post  Brass  Housing Material  Polyester, Glass Filled  Operating Temperature  -55°C ~ 125°C	Pitch - Post	0.100" (2.54mm)
Contact Material - Post  Housing Material  Polyester, Glass Filled  Operating Temperature  -55°C ~ 125°C	Contact Finish - Post	Tin
Housing Material Polyester, Glass Filled Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Post	-
Operating Temperature -55°C ~ 125°C	Contact Material - Post	Brass
	Housing Material	Polyester, Glass Filled
Report errors?	Operating Temperature	-55°C ~ 125°C
		Report errors?

#### **ICO-640-ZLGT Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ICO-640-ZLGT Payment Methods**





















## **ICO-640-ZLGT Shipping Methods**













If you have any question about ICO-640-ZLGT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com