



IDSR.400T Information

Heisener.com

For Reference Only

Part NumberIDSR.400TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 400MA 600VAC/VDC

Package Cylindrical, Alarm Indicating

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IDSR.400T Specifications

Manufacturer Part NumberIDSR.400TManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCylindrical, Alarm IndicatingSeriesPOWR-GARD?, POWR-PRO? IDSRFuse TypeCartridgeCurrent Rating400mAVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Alarm IndicatingSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Alarm Indicating Series POWR-GARD?, POWR-PRO? IDSR Fuse Type Cartridge Current Rating 400mA Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension Class As Cylindrical, Alarm Indicating Size / Dimension Class Cylindrical, Colomm x 127.00mm)	Manufacturer Part Number	IDSR.400T
Electrical, Specialty Fuses Package Cylindrical, Alarm Indicating Series POWR-GARD?, POWR-PRO? IDSR Fuse Type Cartridge Current Rating 400mA Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Electrical, Alarm Indicating Class RK5 Cylindrical, Alarm Indicating	Manufacturer	Littelfuse Inc.
Package Cylindrical, Alarm Indicating Series POWR-GARD?, POWR-PRO? IDSR Fuse Type Cartridge Current Rating 400mA Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Category	Circuit Protection
SeriesPOWR-GARD?, POWR-PRO? IDSRFuse TypeCartridgeCurrent Rating400mAVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Alarm IndicatingSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating400mAVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Alarm IndicatingSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Package	Cylindrical, Alarm Indicating
Current Rating 400mA Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Series	POWR-GARD?, POWR-PRO? IDSR
Voltage Rating - AC Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 60	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 600	Current Rating	400mA
Response Time Applications Electrical, Industrial Features Indicating RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Slow Slow Slow Slow Slow Slow Approvals CE, CSA, Industrial CE, CSA, UL CE, CSA, UL CE, CSA, UL CO, CSA, UL CO, CSA, UL CE,	Voltage Rating - AC	600V
Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Voltage Rating - DC	600V
Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension CE, CSA, UL CRACTOR OF THE PROPERTY OF THE PROPER	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension O.811" Dia x 5.000" L (20.60mm x 127.00mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Operating Temperature	-
Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Alarm Indicating
Report errors?	Size / Dimension	0.811" Dia x 5.000" L (20.60mm x 127.00mm)
		Report errors?

IDSR.400T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IDSR.400T Payment Methods





















IDSR.400T Shipping Methods













If you have any question about IDSR.400T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com