



### **IDSR003.T Information**

Heisener.com

Part NumberIDSR003.TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 3A 600VAC/VDC CYL

Package Cylindrical, Alarm Indicating

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **IDSR003.T Specifications**

Manufacturer Part NumberIDSR003.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionBackageCylindrical, Alarm IndicatingSeriesPOWR-GARD?, POWR-PRO? IDSRFuse TypeCartridgeCurrent Rating3AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Alarm IndicatingSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)Report errors?		
CategoryCircuit ProtectionBeckrical, Specialty FusesPackageCylindrical, Alarm IndicatingSeriesPOWR-GARD?, POWR-PRO? IDSRFuse TypeCartridgeCurrent Rating3AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Alarm IndicatingSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Manufacturer Part Number	IDSR003.T
Beaking Capacity @ Rated Voltage  Electrical, Specialty Fuses  Cylindrical, Alarm Indicating  POWR-GARD?, POWR-PRO? IDSR  Fuse Type Cartridge Current Rating 3A  Voltage Rating - AC 600V  Voltage Rating - DC 600V  Response Time Slow Applications Electrical, Industrial  Features Indicating Class RK5  Approvals CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Cylindrical, Alarm Indicating Size / Dimension  Electrical, Industrial  Color and a color and	Manufacturer	Littelfuse Inc.
Package Cylindrical, Alarm Indicating Series POWR-GARD?, POWR-PRO? IDSR Fuse Type Cartridge Current Rating 3A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Category	Circuit Protection
SeriesPOWR-GARD?, POWR-PRO? IDSRFuse TypeCartridgeCurrent Rating3AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Alarm IndicatingSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating3AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Alarm IndicatingSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Package	Cylindrical, Alarm Indicating
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Signature Signa	Series	POWR-GARD?, POWR-PRO? IDSR
Voltage Rating - AC  Voltage Rating - DC  600V  Response Time  Slow  Applications  Electrical, Industrial  Features  Indicating  Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  60	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Slow  Applications Electrical, Industrial  Features Indicating RK5  Approvals CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  600V  60	Current Rating	3A
Response Time  Applications  Electrical, Industrial  Features  Indicating  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  Slow  Slo	Voltage Rating - AC	600V
Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Voltage Rating - DC	600V
Features Indicating Class RK5  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Applications	Electrical, Industrial
Approvals  CE, CSA, UL  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cylindrical, Alarm Indicating  Size / Dimension  CE, CSA, UL  CHARTON OF THE PROPERTY OF THE PROPER	Features	Indicating
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cylindrical, Alarm Indicating  Size / Dimension  0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cylindrical, Alarm Indicating  Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Operating Temperature	-
Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Alarm Indicating
Report errors?	Size / Dimension	0.811" Dia x 5.000" L (20.60mm x 127.00mm)
		Report errors?

### **IDSR003.T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **IDSR003.T Payment Methods**





















### **IDSR003.T Shipping Methods**













If you have any question about IDSR003.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com