



IDSR04.5T Information

Heisener.com

Part Number IDSR04.5T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 4.5A 600VAC/VDC

Package Cylindrical, Alarm Indicating

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IDSR04.5T Specifications

Manufacturer Part NumberIDSR04.5TManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesPOWR-GARD?, POWR-PRO? IDSRFuse TypeCartridgeCurrent Rating4.5AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Alarm IndicatingSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)Report errors?		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Alarm IndicatingSeriesPOWR-GARD?, POWR-PRO? IDSRFuse TypeCartridgeCurrent Rating4.5AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Alarm IndicatingSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Manufacturer Part Number	IDSR04.5T
Beaking Capacity @ Rated Voltage Electrical, Specialty Fuses Cylindrical, Alarm Indicating POWR-GARD?, POWR-PRO? IDSR Fuse Type Cartridge Current Rating 4.5A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension Electrical, Industrial Color and a color a	Manufacturer	Littelfuse Inc.
Package Cylindrical, Alarm Indicating Series POWR-GARD?, POWR-PRO? IDSR Fuse Type Cartridge Current Rating 4.5A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Deckage Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Category	Circuit Protection
SeriesPOWR-GARD?, POWR-PRO? IDSRFuse TypeCartridgeCurrent Rating4.5AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Alarm IndicatingSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating4.5AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Alarm IndicatingSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Package	Cylindrical, Alarm Indicating
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 4.5A 4.5A 4.5A 4.5A 4.5A 4.5A 4.5A 4.5	Series	POWR-GARD?, POWR-PRO? IDSR
Voltage Rating - AC Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 60	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 600V	Current Rating	4.5A
Response Time Applications Electrical, Industrial Features Indicating RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Slow Slo	Voltage Rating - AC	600V
Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Voltage Rating - DC	600V
Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension CE, CSA, UL CHARTON OF THE PROPERTY OF THE PROPER	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Operating Temperature	-
Package / Case Cylindrical, Alarm Indicating Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Alarm Indicating
Report errors?	Size / Dimension	0.811" Dia x 5.000" L (20.60mm x 127.00mm)
		Report errors?

IDSR04.5T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IDSR04.5T Payment Methods



















IDSR04.5T Shipping Methods













If you have any question about IDSR04.5T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com