



IDSR075.V Information

(A) Heisener.com

Part Number IDSR075.V

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 75A 600VAC/VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IDSR075.V Specifications

Manufacturer Part NumberIDSR075.VManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? IDSRFuse TypeCartridgeCurrent Rating75AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 5.748" L (33.30mm x 146.00mm)		
CategoryCircuit ProtectionBeckrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? IDSRFuse TypeCartridgeCurrent Rating75AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 5.748" L (33.30mm x 146.00mm)	Manufacturer Part Number	IDSR075.V
Electrical, Specialty Fuses Package Cylindrical, Blade Terminals Series POWR-GARD?, POWR-PRO? IDSR Fuse Type Cartridge Current Rating 75A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Electrical, Specialty Fuses Cylindrical, Blade Terminals Size / Dimension Electrical, Industrial Features CU, CSA, UL CU, CO, CSA, UL CU, CSA, UL	Manufacturer	Littelfuse Inc.
Package Cylindrical, Blade Terminals Series POWR-GARD?, POWR-PRO? IDSR Fuse Type Cartridge Current Rating 75A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 5.748" L (33.30mm x 146.00mm)	Category	Circuit Protection
Series POWR-GARD?, POWR-PRO? IDSR Fuse Type Cartridge Current Rating 75A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 5.748" L (33.30mm x 146.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating75AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 5.748" L (33.30mm x 146.00mm)	Package	Cylindrical, Blade Terminals
Current Rating 75A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 5.748" L (33.30mm x 146.00mm)	Series	POWR-GARD?, POWR-PRO? IDSR
Voltage Rating - AC Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 60	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V	Current Rating	75A
Response Time Applications Electrical, Industrial Features Indicating RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Slow Slow Slow Slow Slow Slow Slow Approvals CE, CSA, Industrial CE, CSA, UL - CE, CSA,	Voltage Rating - AC	600V
Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 5.748" L (33.30mm x 146.00mm)	Voltage Rating - DC	600V
Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 5.748" L (33.30mm x 146.00mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 5.748" L (33.30mm x 146.00mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension CE, CSA, UL CHARALLE CONTROLLE CON	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 5.748" L (33.30mm x 146.00mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 5.748" L (33.30mm x 146.00mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 5.748" L (33.30mm x 146.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 5.748" L (33.30mm x 146.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.311" Dia x 5.748" L (33.30mm x 146.00mm)	Mounting Type	Holder
· · ·	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	1.311" Dia x 5.748" L (33.30mm x 146.00mm)
		Report errors?

IDSR075.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IDSR075.V Payment Methods



















IDSR075.V Shipping Methods













If you have any question about IDSR075.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com