



IDSR300.X Information

Heisener.com

Part NumberIDSR300.XManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 300A 600VAC/VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IDSR300.X Specifications

Manufacturer Part NumberIDSR300.XManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? IDSRFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.594" Dia x 7.626" L (65.90mm x 193.70mm)		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? IDSRFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.594" Dia x 7.626" L (65.90mm x 193.70mm)	Manufacturer Part Number	IDSR300.X
Beckage Cylindrical, Blade Terminals Series POWR-GARD?, POWR-PRO? IDSR Fuse Type Cartridge Current Rating 300A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Cylindrical, Blade Terminals Size / Dimension 190KR-PRO? IDSR Cylindrical, Blade Terminals Size / Dimension 2,594" Dia x 7.626" L (65.90mm x 193.70mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD?, POWR-PRO? IDSRFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.594" Dia x 7.626" L (65.90mm x 193.70mm)	Category	Circuit Protection
SeriesPOWR-GARD?, POWR-PRO? IDSRFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.594" Dia x 7.626" L (65.90mm x 193.70mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating300AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.594" Dia x 7.626" L (65.90mm x 193.70mm)	Package	Cylindrical, Blade Terminals
Current Rating 300A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300A 300A 300A 600V 600V	Series	POWR-GARD?, POWR-PRO? IDSR
Voltage Rating - AC Voltage Rating - DC 600V Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 60	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 600V	Current Rating	300A
Response Time Applications Electrical, Industrial Features Indicating RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Slow Slo	Voltage Rating - AC	600V
Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.626" L (65.90mm x 193.70mm)	Voltage Rating - DC	600V
Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.626" L (65.90mm x 193.70mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.626" L (65.90mm x 193.70mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.626" L (65.90mm x 193.70mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.626" L (65.90mm x 193.70mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.626" L (65.90mm x 193.70mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.626" L (65.90mm x 193.70mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.626" L (65.90mm x 193.70mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 2.594" Dia x 7.626" L (65.90mm x 193.70mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	2.594" Dia x 7.626" L (65.90mm x 193.70mm)
		Report errors?

IDSR300.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IDSR300.X Payment Methods



















IDSR300.X Shipping Methods













If you have any question about IDSR300.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com