

### **IF-14-230 Information**

Heisener.com

Part Number IF-14-230

Manufacturer Signal Transformer Category Transformers

Power Transformers

**Description** XFRMR SEMI-TORO 14VA THRU HOLE

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **IF-14-230 Specifications**

Manufacturer Part Number         IF-14-230           Manufacturer         Signal Transformer           Category         Transformers           Package         -           Series         IF           Type         Semi-Toroidal           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 115V, Series 230V           Current - Output (Max)         Parallel 120mA, Series 60mA           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         14 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         67.60mm L x 57.00mm W           Height - Seated (Max)         24.30mm           Voltage - Isolation         4000Vrms           Weight         12 lbs (5.4kg)		
Category         Transformers           Package         -           Series         IF           Type         Semi-Toroidal           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 115V, Series 230V           Current - Output (Max)         Parallel 120mA, Series 60mA           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         14 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         67.60mm L x 57.00mm W           Height - Seated (Max)         24.30mm           Voltage - Isolation         4000Vrms           Weight         12 lbs (5.4kg)	Manufacturer Part Number	IF-14-230
Package Package IF  Type Semi-Toroidal Voltage - Primary Voltage - Secondary (Full Load) Primary Winding(s) Power Tansformers  Parallel 115V, 230V Voltage - Secondary (Full Load) Parallel 120mA, Series 230V Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max I4 VA Mounting Type Through Hole Termination Style Size / Dimension Fixed (Max) PC Pin Size / Dimension Fixed (Max) Voltage - Isolation Weight Power Tansformers  Permination Style Power Transformers  Power Transformers  IF No Power Tansformers  Parallel 120mA, Series 230V Parallel 120mA, Series 60mA Primary Winding(s) Pual Power Secondary Winding(s) Pual Power - Max Primary Winding(s) Power - Max Primary Winding(s) Power - Max Primary Winding(s) Power - Max Parallel 120mA, Series 230V Parallel 120m	Manufacturer	Signal Transformer
Package         -           Series         IF           Type         Semi-Toroidal           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 115V, Series 230V           Current - Output (Max)         Parallel 120mA, Series 60mA           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         14 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         67.60mm L x 57.00mm W           Height - Seated (Max)         24.30mm           Voltage - Isolation         4000Vrms           Weight         12 lbs (5.4kg)	Category	Transformers
SeriesIFTypeSemi-ToroidalVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 120mA, Series 60mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max14 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension67.60mm L x 57.00mm WHeight - Seated (Max)24.30mmVoltage - Isolation4000VrmsWeight12 lbs (5.4kg)		Power Transformers
Type Semi-Toroidal  Voltage - Primary 115V, 230V  Voltage - Secondary (Full Load) Parallel 115V, Series 230V  Current - Output (Max) Parallel 120mA, Series 60mA  Primary Winding(s) Dual  Secondary Winding(s) Dual  Center Tap No  Power - Max 14 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 67.60mm L x 57.00mm W  Height - Seated (Max) 24.30mm  Voltage - Isolation 4000Vrms  Weight 12 lbs (5.4kg)	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 115V, 230V  Current - Output (Max)  Parallel 120mA, Series 60mA  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  14 VA  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  Height - Seated (Max)  Voltage - Isolation  Weight  115V, 230V  Parallel 115V, Series 230V  Parallel 120mA, Series 60mA  Pual  Pual  Pual  Farillel 120mA, Series 60mA  Pual  Pual  Pual  Farillel 120mA, Series 60mA  Pual  Pual  Farillel 120mA, Series 60mA  Pual  Pual  Formination Style  Formination Style  PC Pin  Size / Dimension  4000Vrms  Weight  12 lbs (5.4kg)	Series	IF
Voltage - Secondary (Full Load)  Current - Output (Max)  Parallel 120mA, Series 230V  Parallel 120mA, Series 60mA  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  14 VA  Mounting Type  Through Hole  Termination Style  Size / Dimension  67.60mm L x 57.00mm W  Height - Seated (Max)  Voltage - Isolation  Weight  Parallel 115V, Series 230V  Parallel 120mA, Series 230V  Pual  A VA	Туре	Semi-Toroidal Semi-Toroidal
Current - Output (Max)Parallel 120mA, Series 60mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max14 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension67.60mm L x 57.00mm WHeight - Seated (Max)24.30mmVoltage - Isolation4000VrmsWeight12 lbs (5.4kg)	Voltage - Primary	115V, 230V
Primary Winding(s)  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  14 VA  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  67.60mm L x 57.00mm W  Height - Seated (Max)  Voltage - Isolation  Weight  Dual  No  14 VA  No  14 VA  14 VA  14 VA  15 VA  16 VA  16 VA  17 VA  18 VA  19 VA  19 VA  19 VA  10 VA  11 VA  12 lbs (5.4kg)	Voltage - Secondary (Full Load)	Parallel 115V, Series 230V
Secondary Winding(s)DualCenter TapNoPower - Max14 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension67.60mm L x 57.00mm WHeight - Seated (Max)24.30mmVoltage - Isolation4000VrmsWeight12 lbs (5.4kg)	Current - Output (Max)	Parallel 120mA, Series 60mA
Center Tap No  Power - Max 14 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 67.60mm L x 57.00mm W  Height - Seated (Max) 24.30mm  Voltage - Isolation 4000Vrms  Weight 12 lbs (5.4kg)	Primary Winding(s)	Dual
Power - Max  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  67.60mm L x 57.00mm W  Height - Seated (Max)  Voltage - Isolation  4000Vrms  Weight  12 lbs (5.4kg)	Secondary Winding(s)	Dual
Mounting Type Through Hole  PC Pin  Size / Dimension 67.60mm L x 57.00mm W  Height - Seated (Max) 24.30mm  Voltage - Isolation 4000Vrms  Weight 12 lbs (5.4kg)	Center Tap	No
Termination Style PC Pin Size / Dimension 67.60mm L x 57.00mm W Height - Seated (Max) 24.30mm Voltage - Isolation 4000Vrms Weight 12 lbs (5.4kg)	Power - Max	14 VA
Size / Dimension 67.60mm L x 57.00mm W  Height - Seated (Max) 24.30mm  Voltage - Isolation 4000Vrms  Weight 12 lbs (5.4kg)	Mounting Type	Through Hole
Height - Seated (Max)  Voltage - Isolation  Weight  24.30mm  4000Vrms  12 lbs (5.4kg)	Termination Style	PC Pin
Voltage - Isolation 4000Vrms Weight 12 lbs (5.4kg)	Size / Dimension	67.60mm L x 57.00mm W
Weight 12 lbs (5.4kg)	Height - Seated (Max)	24.30mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	12 lbs (5.4kg)
		Report errors?

#### IF-14-230 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### IF-14-230 Payment Methods


































If you have any question about IF-14-230, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com