

IF-18-12 Information

Heisener.com

Part Number IF-18-12

Manufacturer Signal Transformer

Category Transformers
Power Transformers

Description XFRMR SEMI-TORO 18VA THRU HOLE

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IF-18-12 Specifications

Manufacturer IF-18-12 Manufacturer Signal Transformer Category Transformers Package - Series IF Type Semi-Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6V, Series 12V Current - Output (Max) Parallel 3A, Series 1.5A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 18 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 67.60mm L x 57.00mm W Height - Seated (Max) 27.60mm Voltage - Isolation 4000Vrms Weight 15 lbs (6.8kg)		
Category Transformers Power Transformers Package - Series IF Type Semi-Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6V, Series 12V Current - Output (Max) Parallel 3A, Series 1.5A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 18 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 67.60mm L x 57.00mm W Height - Seated (Max) 27.60mm Voltage - Isolation 4000Vrms Weight 15 lbs (6.8kg)	Manufacturer Part Number	IF-18-12
Package Power Transformers Package Frimary Poltage - Primary Poltage - Secondary (Full Load) Primary Winding(s) Power Transformers Parallel 6V, Series 12V Parallel 3A, Series 1.5A Primary Winding(s) Poual Secondary Winding(s) Poual Power - Max Power - Max Power - Max Power - Max Primation Style Por Pin Size / Dimension Frimation Style Port of 7.60mm L x 57.00mm W Poltage - Isolation Power - Isolation Po	Manufacturer	Signal Transformer
Package - Series IF Type Semi-Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6V, Series 12V Current - Output (Max) Parallel 3A, Series 1.5A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 18 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 67.60mm L x 57.00mm W Height - Seated (Max) 27.60mm Voltage - Isolation 4000Vrms Weight 15 lbs (6.8kg)	Category	Transformers
Series IF Type Semi-Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6V, Series 12V Current - Output (Max) Parallel 3A, Series 1.5A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 18 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 67.60mm L x 57.00mm W Height - Seated (Max) 27.60mm Voltage - Isolation 4000Vrms Weight 15 lbs (6.8kg)		Power Transformers
Type Semi-Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 6V, Series 12V Current - Output (Max) Parallel 3A, Series 1.5A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 18 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 67.60mm L x 57.00mm W Height - Seated (Max) 27.60mm Voltage - Isolation 4000Vrms Weight 15 lbs (6.8kg)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 6V, Series 12V Current - Output (Max) Parallel 3A, Series 1.5A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 18 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 15 lbs (6.8kg)	Series	IF
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 6V, Series 12V Parallel 3A, Series 1.5A Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 18 VA Mounting Type Through Hole Termination Style Size / Dimension 67.60mm L x 57.00mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 6V, Series 12V Parallel 6V, Series 1.5A Primary Winding(s) Dual 80 Center Tap No 4000Vrms 4000Vrms 15 lbs (6.8kg)	Туре	Semi-Toroidal
Current - Output (Max)Parallel 3A, Series 1.5APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max18 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension67.60mm L x 57.00mm WHeight - Seated (Max)27.60mmVoltage - Isolation4000VrmsWeight15 lbs (6.8kg)	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 18 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 67.60mm L x 57.00mm W Height - Seated (Max) Voltage - Isolation Weight Dual No 18 VA 18 VA Through Hole 27.60mm 4000Vrms 15 lbs (6.8kg)	Voltage - Secondary (Full Load)	Parallel 6V, Series 12V
Secondary Winding(s)DualCenter TapNoPower - Max18 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension67.60mm L x 57.00mm WHeight - Seated (Max)27.60mmVoltage - Isolation4000VrmsWeight15 lbs (6.8kg)	Current - Output (Max)	Parallel 3A, Series 1.5A
Center Tap No Power - Max 18 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 67.60mm L x 57.00mm W Height - Seated (Max) 27.60mm Voltage - Isolation 4000Vrms Weight 15 lbs (6.8kg)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 67.60mm L x 57.00mm W Height - Seated (Max) Voltage - Isolation Weight 15 lbs (6.8kg)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 67.60mm L x 57.00mm W Height - Seated (Max) 27.60mm Voltage - Isolation 4000Vrms Weight 15 lbs (6.8kg)	Center Tap	No
Termination Style PC Pin Size / Dimension 67.60mm L x 57.00mm W Height - Seated (Max) 27.60mm Voltage - Isolation 4000Vrms Weight 15 lbs (6.8kg)	Power - Max	18 VA
Size / Dimension 67.60mm L x 57.00mm W Height - Seated (Max) 27.60mm Voltage - Isolation 4000Vrms Weight 15 lbs (6.8kg)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 27.60mm 4000Vrms 15 lbs (6.8kg)	Termination Style	PC Pin
Voltage - Isolation 4000Vrms Weight 15 lbs (6.8kg)	Size / Dimension	67.60mm L x 57.00mm W
Weight 15 lbs (6.8kg)	Height - Seated (Max)	27.60mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	15 lbs (6.8kg)
· · · · · · · · · · · · · · · · · · ·		Report errors?

IF-18-12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IF-18-12 Payment Methods





















IF-18-12 Shipping Methods













If you have any question about IF-18-12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com