

ILR3FAD2L0W

ILR3FAD2L0W Information

ry,heis aner.com	Part Number Manufacturer Category Description Package	ILR3FAD2L0W APEM Inc. Switches Pushbutton Switches SWITCH PUSHBUTTON SPST-NO 2A 24V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ILR3FAD2L0W Specifications

SeriesILTypeStandard, IlluminatedCircuitSPST-NOSwitch FunctionOff-MomCurrent Rating2A (DC)Voltage Rating - AC-Voltage Rating - DC24VActuator TypeBlackCloor - Actuator/CapILED, WhiteIllumination Voltage (Nominal)3.35 VDCMounting TypeHanel Mount, FrontTermination StyleWire LeadsIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed Terminals			
CategorySwitchesPackage-PackageILSeriesILTypeStandard, IlluninatedCircuitSPST-NOSwitch FunctionOff-MomCurrent Rating2A (DC)Voltage Rating - DC24VColor - Actuator/CapBlackIllunination Type, ColorLED, WhiteIllunination Voltage (Nominal)3.35 VDCMounting TypePanel Mount, FrontIngress ProtectionPory Sealed TerminalsFaturesPory Sealed TerminalsPanel Cuotu DimensionsSicolar - 13.60mm Dia	Manufacturer Part Number	ILR3FAD2L0W	
Pushbutton SwitchesPackage-SeriesILTypeStandard, IlluminatedCircuitSPST-NOSwitch FunctionOff-MomCurrent Rating2A (DC)Voltage Rating - AC-Voltage Rating - DC24VActuator TypeBlackIllumination Voltage (Nominal)3.35 VDCIllumination Voltage (Nominal)Sits VDCMounting TypePanel Mount, FrontTermination StyleIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Manufacturer	APEM Inc.	
Package-SeriesILTypeStandard, IlluminatedCircuitSPST-NOSwitch FunctionOff-MornCurrent Rating2A (DC)Voltage Rating - AC-Voltage Rating - DCAdudton, DomedColor - Actuator/CapBlackIllumination Type, ColorLED, WhiteIllumination Voltage (Nominal)3.55 VDCMounting TypePanel Mount, FrontTermination StyleIPO - Dust Tight, WaterproofFaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Category	Switches	
SeriesILTypeStandard, IlluminatedCircuitSPST-NOSwitch FunctionOff-MomCurrent Rating2A (DC)Voltage Rating - AC-Voltage Rating - DC24VActuator TypeBlackClor - Actuator/CapIED, WhiteIllumination Voltage (Nominal)3.35 VDCMounting TypePanel Mount, FrontIngress ProtectionIPG7 - Dust Tight, WaterproofFaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia		Pushbutton Switches	
TypeStandard, IlluminatedCircuitSPST-NOSwitch FunctionOff-MomCurrent Rating2A (DC)Voltage Rating - AC-Voltage Rating - DC24VActuator TypeBlackColor - Actuator/CapBlackIllumination Voltage (Nominal)3.35 VDCMounting TypeVire LeadsIngress ProtectionIPG7 - Dust Tight, WaterproofFeaturesEpoy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Package	-	
CircuitSPST-NOSwitch FunctionOff-MomCurrent Rating2A (DC)Voltage Rating - AC-Voltage Rating - DC24VActuator TypeRound, Button, DomedColor - Actuator/CapBlackIllumination Type, Color3.35 VDCMounting TypePanel Mount, FrontTermination StyleWire LeadsIngress ProtectionP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Series	IL	
Switch FunctionOff-MomCurrent Rating2A (DC)Voltage Rating - AC-Voltage Rating - DC24VActuator TypeRound, Button, DomedColor - Actuator/CapBlackIllumination Type, ColorLED, WhiteIllumination Voltage (Nominal)3.35 VDCMounting TypeWire LeadsIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Туре	Standard, Illuminated	
Current Rating2A (DC)Voltage Rating - AC-Voltage Rating - DC24VActuator TypeRound, Button, DomedColor - Actuator/CapBlackIllumination Type, ColorLED, WhiteIllumination Voltage (Nominal)3.35 VDCMounting TypePanel Mount, FrontTermination StyleIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Circuit	SPST-NO	
Voltage Rating - AC-Voltage Rating - DC24VActuator TypeRound, Button, DomedColor - Actuator/CapBlackIllumination Type, ColorLED, WhiteIllumination Voltage (Nominal)3.35 VDCMounting TypePanel Mount, FrontTermination StyleIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Switch Function	Off-Mom	
Voltage Rating - DC24VActuator TypeRound, Button, DomedColor - Actuator/CapBlackIllumination Type, ColorLED, WhiteIllumination Voltage (Nominal)3.35 VDCMounting TypePanel Mount, FrontTermination StyleWire LeadsIngress ProtectionP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Current Rating	2A (DC)	
Actuator TypeRound, Button, DomedColor - Actuator/CapBlackIllumination Type, ColorLED, WhiteIllumination Voltage (Nominal)3.35 VDCMounting TypePanel Mount, FrontTermination StyleWire LeadsIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Voltage Rating - AC	-	
Color - Actuator/CapBlackIllumination Type, ColorLED, WhiteIllumination Voltage (Nominal)3.35 VDCMounting TypePanel Mount, FrontTermination StyleWire LeadsIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Voltage Rating - DC	24V	
Illumination Type, ColorLED, WhiteIllumination Voltage (Nominal)3.35 VDCMounting TypePanel Mount, FrontTermination StyleWire LeadsIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Actuator Type	Round, Button, Domed	
Illumination Voltage (Nominal)3.35 VDCMounting TypePanel Mount, FrontTermination StyleWire LeadsIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Color - Actuator/Cap	Black	
Mounting TypePanel Mount, FrontTermination StyleWire LeadsIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Illumination Type, Color	LED, White	
Termination StyleWire LeadsIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Illumination Voltage (Nominal)	3.35 VDC	
Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Mounting Type	Panel Mount, Front	
FeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Termination Style	Wire Leads	
Panel Cutout Dimensions Circular - 13.60mm Dia	Ingress Protection	IP67 - Dust Tight, Waterproof	
	Features	Epoxy Sealed Terminals	
Report errors?	Panel Cutout Dimensions	Circular - 13.60mm Dia	
			Report errors?

ILR3FAD2L0W Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ILR3FAD2L0W Payment Methods



ILR3FAD2L0W Shipping Methods



If you have any question about ILR3FAD2L0W, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com