



IM00JR Information

www.heisener.com

For Reference Only

Part Number IM00JR

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Signal Relays, Up to 2 Amps

RELAY TELECOM DPDT 2A 1.5V Description

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IM00JR Specifications

Manufacturer Part NumberIM00JRManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysSignal Relays, Up to 2 AmpsPackage-SeriesIM, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current93.3mACoil Voltage1.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)1.13 VDCTurn Off Voltage (Min)0.15 VDC
Category Relays Signal Relays, Up to 2 Amps Package - Series IM, AXICOM Relay Type Telecom Coil Type Non Latching Coil Current 93.3mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.13 VDC
Package - Series IM, AXICOM Relay Type Telecom Coil Type Non Latching Coil Current 93.3mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage (Max) 1.13 VDC
Package - IM, AXICOM Relay Type Telecom Coil Type Non Latching Coil Current 93.3mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.13 VDC
SeriesIM, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current93.3mACoil Voltage1.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)1.13 VDC
Relay TypeTelecomCoil TypeNon LatchingCoil Current93.3mACoil Voltage1.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)1.13 VDC
Coil Type Non Latching Coil Current 93.3mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.13 VDC
Coil Current 93.3mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.13 VDC
Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.13 VDC
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.13 VDC
Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.13 VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.13 VDC
Turn On Voltage (Max) 1.13 VDC
Turn Off Voltage (Min) 0.15 VDC
Operate Time 3ms
Release Time 3ms
Features Sealed - Hermetically
Mounting Type Surface Mount
Termination Style J Lead
Report errors?

IM00JR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IM00JR Payment Methods



















IM00JR Shipping Methods













If you have any question about IM00JR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com