



INA215CIRSWT Information

Heisener.com

For Reference Only

Part Number INA215CIRSWT

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OP AMP CURR SENSE 10UQFN

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









INA215CIRSWT Specifications

Manufacturer Part Number INA215CIRSWT Manufacturer Texas Instruments Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package - Series Zero-Drift Amplifier Type Current Sense Number of Circuits 2 Output Type - Slew Rate 0.4 V/μs Gain Bandwidth Product 40kHz -3db Bandwidth - Current - Input Bias 28μA Voltage - Input Offset 0.55μV Current - Supply 65μA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 2.7 V ~ 26 V Operating Temperature -40°C ~ 125°C Mounting Type - Package / Case - Supplier Device Package -		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package - Series Zero-Drift Amplifier Type Current Sense Number of Circuits 2 Output Type - Slew Rate 0.4 V/µs Gain Bandwidth Product 40kHz -3db Bandwidth - Current - Input Bias 28µA Voltage - Input Offset 0.55µV Current - Supply 65µA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 2.7 V ~ 26 V Operating Temperature -40°C ~ 125°C Mounting Type - Package / Case - Supplier Device Package -	Manufacturer Part Number	INA215CIRSWT
Package-SeriesZero-DriftAmplifier TypeCurrent SenseNumber of Circuits2Output Type-Slew Rate $0.4 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 40kHz -3db Bandwidth-Current - Input Bias $28\mu\text{A}$ Voltage - Input Offset $0.55\mu\text{V}$ Current - Output / Channel-Voltage - Supply, Single/Dual (\pm) $2.7 \text{ V} \sim 26 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type-Package / Case-Supplier Device Package-	Manufacturer	Texas Instruments
Package - Series Zero-Drift Amplifier Type Current Sense Number of Circuits 2 Output Type - Slew Rate 0.4 V/μs Gain Bandwidth Product 40kHz -3db Bandwidth - Current - Input Bias 28μA Voltage - Input Offset 0.55μV Current - Supply 65μA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 2.7 V ~ 26 V Operating Temperature -40°C ~ 125°C Mounting Type - Package / Case - Supplier Device Package -	Category	Integrated Circuits (ICs)
SeriesZero-DriftAmplifier TypeCurrent SenseNumber of Circuits2Output Type-Slew Rate $0.4 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 40kHz -3db Bandwidth-Current - Input Bias $28\mu\text{A}$ Voltage - Input Offset $0.55\mu\text{V}$ Current - Supply $65\mu\text{A}$ Current - Output / Channel-Voltage - Supply, Single/Dual (±) $2.7 \text{ V} \sim 26 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type-Package / Case-Supplier Device Package-		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier TypeCurrent SenseNumber of Circuits2Output Type-Slew Rate0.4 V/μsGain Bandwidth Product40kHz-3db Bandwidth-Current - Input Bias28μAVoltage - Input Offset0.55μVCurrent - Supply65μACurrent - Output / Channel-Voltage - Supply, Single/Dual (±)2.7 V ~ 26 VOperating Temperature-40°C ~ 125°CMounting Type-Package / Case-Supplier Device Package-	Package	-
Number of Circuits2Output Type-Slew Rate 0.4 V/μs Gain Bandwidth Product 40kHz -3db Bandwidth-Current - Input Bias $28\mu\text{A}$ Voltage - Input Offset $0.55\mu\text{V}$ Current - Supply $65\mu\text{A}$ Current - Output / Channel-Voltage - Supply, Single/Dual (±) $2.7 \text{ V} \sim 26 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type-Package / Case-Supplier Device Package-	Series	Zero-Drift
Output Type - Slew Rate 0.4 V/μs Gain Bandwidth Product 40kHz -3db Bandwidth - Current - Input Bias 28μA Voltage - Input Offset 0.55μV Current - Supply 65μA Current - Output / Channel - Voltage - Supply, Single/Dual (±) 2.7 V ~ 26 V Operating Temperature -40°C ~ 125°C Mounting Type - Package / Case - Supplier Device Package -	Amplifier Type	Current Sense
Slew Rate $0.4 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 40kHz -3db Bandwidth Current - Input Bias $28\mu\text{A}$ Voltage - Input Offset $0.55\mu\text{V}$ Current - Supply $65\mu\text{A}$ Current - Output / Channel Voltage - Supply, Single/Dual (\pm) $2.7 \text{ V} \sim 26 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type Package / Case Supplier Device Package	Number of Circuits	2
Gain Bandwidth Product $40kHz$ -3db Bandwidth - Current - Input Bias $28\mu A$ Voltage - Input Offset $0.55\mu V$ Current - Supply $65\mu A$ Current - Output / Channel - Voltage - Supply, Single/Dual (±) $2.7 \ V \sim 26 \ V$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Mounting Type - Package / Case - Supplier Device Package -	Output Type	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Slew Rate	0.4 V/μs
Current - Input Bias $28\mu A$ Voltage - Input Offset $0.55\mu V$ Current - Supply $65\mu A$ Current - Output / Channel-Voltage - Supply, Single/Dual (\pm) $2.7 \text{ V} \sim 26 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type-Package / Case-Supplier Device Package-	Gain Bandwidth Product	40kHz
Voltage - Input Offset $0.55\mu V$ Current - Supply $65\mu A$ Current - Output / Channel - Voltage - Supply, Single/Dual (±) $2.7 \ V \sim 26 \ V$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Mounting Type - Package / Case - Supplier Device Package	-3db Bandwidth	-
Current - Supply $65\mu A$ Current - Output / Channel - Voltage - Supply, Single/Dual (±) $2.7 \text{ V} \sim 26 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type - Package / Case - Supplier Device Package -	Current - Input Bias	28μΑ
Current - Output / Channel - Voltage - Supply, Single/Dual (±) 2.7 V ~ 26 V Operating Temperature -40°C ~ 125°C Mounting Type - Package / Case - Supplier Device Package -	Voltage - Input Offset	$0.55\mu V$
Voltage - Supply, Single/Dual (\pm) 2.7 V ~ 26 V Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type - Package / Case - Supplier Device Package -	Current - Supply	65μΑ
Operating Temperature -40°C ~ 125°C Mounting Type - Package / Case - Supplier Device Package -	Current - Output / Channel	-
Mounting Type - Package / Case - Supplier Device Package -	Voltage - Supply, Single/Dual (±)	2.7 V ~ 26 V
Package / Case - Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
Supplier Device Package -	Mounting Type	-
	Package / Case	-
Report errors?	Supplier Device Package	-
		Report errors?

INA215CIRSWT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

INA215CIRSWT Payment Methods



















INA215CIRSWT Shipping Methods













If you have any question about INA215CIRSWT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com