



INN3268C-H207-TL Information



For Reference Only

Part Number INN3268C-H207-TL

Manufacturer Power Integrations

Category Integrated Circuits (ICs)

PMIC - AC DC Converters, Offline Switchers

Description IC OFFLINE SWITCH SR CONTROL

Package 24-PowerSMD Module (0.425", 10.80mm Width),

1 / Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









INN3268C-H207-TL Specifications

Manufacturer Part Number INN3268C-H207-TL Manufacturer Power Integrations Category Integrated Circuits (ICs) Package 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Series InnoSwitch™3-CP Output Isolation Isolated Internal Switch(s) Yes Voltage - Breakdown 650V Topology Flyback, Secondary Side SR Voltage - Surply (Vcc/Vdd) - Duty Cycle - Frequency - Switching 100kHz Power (Watts) 50W Fault Protection Current Limiting, Over Temperature, Over Voltage Control Features - Operating Temperature -40°C ~ 150°C (TJ) Package / Case 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Supplier Device Package InSOP-24D Mounting Type Surface Mount		
Category Integrated Circuits (ICs) PMIC - AC DC Converters, Offline Switchers 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Series InnoSwitchTM3-CP Output Isolation Isolated Internal Switch(s) Yes Voltage - Breakdown 650V Topology Flyback, Secondary Side SR Voltage - Start Up - Voltage - Supply (Vcc/Vdd) - Duty Cycle - Frequency - Switching 100kHz Power (Watts) Fault Protection Current Limiting, Over Temperature, Over Voltage Control Features Operating Temperature -40°C ~ 150°C (TJ) Package / Case Supplier Device Package Mounting Type Surface Mount	Manufacturer Part Number	INN3268C-H207-TL
Package 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Series InnoSwitch™3-CP Output Isolation Isolated Internal Switch(s) Yes Voltage - Breakdown 650V Topology Flyback, Secondary Side SR Voltage - Start Up - Voltage - Supply (Vcc/Vdd) - Duty Cycle - Frequency - Switching 100kHz Power (Watts) 50W Fault Protection Current Limiting, Over Temperature, Over Voltage Control Features - Operating Temperature -40°C ~ 150°C (TJ) Package / Case 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Supplier Device Package InSOP-24D Mounting Type Surface Mount	Manufacturer	Power Integrations
Package24-PowerSMD Module (0.425", 10.80mm Width), 17 LeadsSeriesInnoSwitch™3-CPOutput IsolationIsolatedInternal Switch(s)YesVoltage - Breakdown650VTopologyFlyback, Secondary Side SRVoltage - Start Up-Voltage - Supply (Vcc/Vdd)-Duty Cycle-Frequency - Switching100kHzPower (Watts)50WFault ProtectionCurrent Limiting, Over Temperature, Over VoltageControl Features-Operating Temperature-40°C ~ 150°C (TJ)Package / Case24-PowerSMD Module (0.425", 10.80mm Width), 17 LeadsSupplier Device PackageInSOP-24DMounting TypeSurface Mount	Category	Integrated Circuits (ICs)
SeriesInnoSwitch™3-CPOutput IsolationIsolatedInternal Switch(s)YesVoltage - Breakdown650VTopologyFlyback, Secondary Side SRVoltage - Start Up-Voltage - Supply (Vcc/Vdd)-Duty Cycle-Frequency - Switching100kHzPower (Watts)50WFault ProtectionCurrent Limiting, Over Temperature, Over VoltageControl Features-Operating Temperature-40°C ~ 150°C (TJ)Package / Case24-PowerSMD Module (0.425", 10.80mm Width), 17 LeadsSupplier Device PackageInSOP-24DMounting TypeSurface Mount		PMIC - AC DC Converters, Offline Switchers
Output IsolationIsolatedInternal Switch(s)YesVoltage - Breakdown650VTopologyFlyback, Secondary Side SRVoltage - Start Up-Voltage - Supply (Vcc/Vdd)-Duty Cycle-Frequency - Switching100kHzPower (Watts)50WFault ProtectionCurrent Limiting, Over Temperature, Over VoltageControl Features-Operating Temperature-40°C ~ 150°C (TJ)Package / Case24-PowerSMD Module (0.425", 10.80mm Width), 17 LeadsSupplier Device PackageInSOP-24DMounting TypeSurface Mount	Package	24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads
Internal Switch(s) Voltage - Breakdown 650V Topology Flyback, Secondary Side SR Voltage - Start Up - Voltage - Supply (Vcc/Vdd) - Duty Cycle Frequency - Switching Power (Watts) Fault Protection Current Limiting, Over Temperature, Over Voltage Control Features Operating Temperature -40°C ~ 150°C (TJ) Package / Case Supplier Device Package Mounting Type Surface Mount	Series	InnoSwitch TM 3-CP
Voltage - Breakdown Topology Flyback, Secondary Side SR Voltage - Start Up - Voltage - Supply (Vcc/Vdd) Duty Cycle Frequency - Switching Power (Watts) Fault Protection Current Limiting, Over Temperature, Over Voltage Control Features Operating Temperature -40°C ~ 150°C (TJ) Package / Case 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Supplier Device Package Mounting Type Surface Mount	Output Isolation	Isolated
Topology Flyback, Secondary Side SR Voltage - Start Up - Voltage - Supply (Vcc/Vdd) Duty Cycle Frequency - Switching 100kHz Power (Watts) Fault Protection Current Limiting, Over Temperature, Over Voltage Control Features Operating Temperature -40°C ~ 150°C (TJ) Package / Case 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Supplier Device Package Mounting Type Surface Mount	Internal Switch(s)	Yes
Voltage - Start Up Voltage - Supply (Vcc/Vdd) Duty Cycle Frequency - Switching 100kHz Power (Watts) Fault Protection Current Limiting, Over Temperature, Over Voltage Control Features Operating Temperature -40°C ~ 150°C (TJ) Package / Case 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Supplier Device Package Mounting Type Surface Mount	Voltage - Breakdown	650V
Voltage - Supply (Vcc/Vdd) Duty Cycle - Frequency - Switching 100kHz Power (Watts) 50W Fault Protection Current Limiting, Over Temperature, Over Voltage Control Features - Operating Temperature -40°C ~ 150°C (TJ) Package / Case 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Supplier Device Package InSOP-24D Mounting Type Surface Mount	Topology	Flyback, Secondary Side SR
Duty Cycle Frequency - Switching 100kHz Power (Watts) 50W Fault Protection Current Limiting, Over Temperature, Over Voltage Control Features Operating Temperature -40°C ~ 150°C (TJ) Package / Case 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Supplier Device Package InSOP-24D Mounting Type Surface Mount	Voltage - Start Up	-
Frequency - Switching Power (Watts) Fault Protection Current Limiting, Over Temperature, Over Voltage Control Features Operating Temperature -40°C ~ 150°C (TJ) Package / Case 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Supplier Device Package InSOP-24D Mounting Type Surface Mount	Voltage - Supply (Vcc/Vdd)	-
Power (Watts) Fault Protection Current Limiting, Over Temperature, Over Voltage Control Features Operating Temperature -40°C ~ 150°C (TJ) Package / Case 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Supplier Device Package InSOP-24D Mounting Type Surface Mount	Duty Cycle	-
Fault Protection Current Limiting, Over Temperature, Over Voltage Control Features - Operating Temperature -40°C ~ 150°C (TJ) Package / Case 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Supplier Device Package InSOP-24D Mounting Type Surface Mount	Frequency - Switching	100kHz
Control Features Operating Temperature -40°C ~ 150°C (TJ) Package / Case 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Supplier Device Package InSOP-24D Mounting Type Surface Mount	Power (Watts)	50W
Operating Temperature -40°C ~ 150°C (TJ) Package / Case 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Supplier Device Package InSOP-24D Mounting Type Surface Mount	Fault Protection	Current Limiting, Over Temperature, Over Voltage
Package / Case 24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads Supplier Device Package InSOP-24D Mounting Type Surface Mount	Control Features	-
Supplier Device Package InSOP-24D Mounting Type Surface Mount	Operating Temperature	-40°C ~ 150°C (TJ)
Mounting Type Surface Mount	Package / Case	24-PowerSMD Module (0.425", 10.80mm Width), 17 Leads
	Supplier Device Package	InSOP-24D
Report errors?	Mounting Type	Surface Mount
		Report errors?

INN3268C-H207-TL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

INN3268C-H207-TL Payment Methods



















INN3268C-H207-TL Shipping Methods













If you have any question about INN3268C-H207-TL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com