

IPC1SAD1L0G

equest a Quote

IPC1SAD1L0G Information

Contraction of the second seco	Part Number	IPC1SAD1L0G
	Manufacturer	APEM Inc.
	Category	Switches Pushbutton Switches
	Description	SWITCH PUSHBUTTON SPST 4A 12V
	Package	-
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



IPC1SAD1L0G Specifications

SeriesIPTypeStandard, IlluminatedTypeStandard, IlluminatedCircuitSPSTSwitch FunctionOff-OnCurrent Rating2A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DCSquare, ButtonColor - Actuator/CapBlueIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCMounting TypeSolder LugIngress ProtectionSolder LugFeaturesEpoy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia		
CategorySwitchesPackage-SeriesIPTypeStandard, IlluminatedCircuitSPSTSwitch FunctionOff-OnCurrent Rating2A (AC), 4A (DC)Voltage Rating - AC12VVoltage Rating - DCSlauge Rating - DCCirol - Actuator/CapBlueIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCMouting TypeSolder LugIngress ProtectionFor Just Tight, WaterproofFeaturesFory Sealed TerminalsPanel Cutout DimensionsGrocultar - J. Scolder LugPanel Cutout DimensionsCircular - J. Scolder Lug	Manufacturer Part Number	IPC1SAD1L0G
Pushbutton SwitchesPackage-SeriesIPTypeStandard, IlluminatedCircuitSPSTSwitch FunctionOff-OnCurrent Rating2A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DCSquare, ButtonColor - Actuator/CapBlueIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCMounting TypeSolder LugIngress ProtectionFory Sealed TerminalsFaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Manufacturer	APEM Inc.
Package-SeriesIPTypeStandard, IlluminatedCircuitSPSTSwitch FunctionOff-OnCurrent Rating2A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DCSquare, ButtonActuator TypeSquare, ButtonColor - Actuator/CapBlueIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCMounting TypeSolder LugIngress ProtectionFord Sulf LugFaturesEpoy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Category	Switches
SeriesIPTypeStandard, IlluminatedTypeStandard, IlluminatedCircuitSPSTSwitch FunctionOff-OnCurrent Rating2A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DCSquare, ButtonColor - Actuator/CapBlueIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCMounting TypeSolder LugIngress ProtectionSolder LugFeaturesEpoy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia		Pushbutton Switches
TypeStandard, IlluminatedCircuitSPSTSwitch FunctionOff-OnCurrent Rating2A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC12VActuator TypeSquare, ButtonColor - Actuator/CapBlueIllumination Voltage (Nominal)2 VDCMounting TypeSolder LugMounting TypeSolder LugIngress ProtectionForsy Scaled TerminalsFeaturesEpoy Scaled TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Package	-
CircuitSPSTSwitch FunctionOff-OnCurrent Rating2A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC12VActuator TypeSquare, ButtonColor - Actuator/CapBlueIllumination Type, Color2 VDCMounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Series	IP
Switch FunctionOff-OnCurrent Rating2A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC12VActuator TypeSquare, ButtonColor - Actuator/CapBlueIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCMounting TypeSolder LugIngress ProtectionP67 - Dust Tight, WaterproofFeaturesEpoxy Scaled TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Туре	Standard, Illuminated
Current Rating2A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC12VActuator TypeSquare, ButtonColor - Actuator/CapBlueIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCMounting TypeSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Circuit	SPST
Voltage Rating - AC125VVoltage Rating - DC12VActuator TypeSquare, ButtonColor - Actuator/CapBlueIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCMounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Switch Function	Off-On
Voltage Rating - DC12VActuator TypeSquare, ButtonColor - Actuator/CapBlueIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCMounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionH67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsYene Mount DimensionsCircular - 13.60mm Dia	Current Rating	2A (AC), 4A (DC)
Actuator TypeSquare, ButtonActuator TypeBlueColor - Actuator/CapLED, GreenIllumination Type, Color2 VDCMounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Voltage Rating - AC	125V
Color - Actuator/CapBlueIllumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCMounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Voltage Rating - DC	12V
Illumination Type, ColorLED, GreenIllumination Voltage (Nominal)2 VDCMounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Actuator Type	Square, Button
Illumination Voltage (Nominal)2 VDCMounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Color - Actuator/Cap	Blue
Mounting TypePanel Mount, FrontTermination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Illumination Type, Color	LED, Green
Termination StyleSolder LugIngress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Illumination Voltage (Nominal)	2 VDC
Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Mounting Type	Panel Mount, Front
FeaturesEpoxy Sealed TerminalsPanel Cutout DimensionsCircular - 13.60mm Dia	Termination Style	Solder Lug
Panel Cutout Dimensions Circular - 13.60mm Dia	Ingress Protection	IP67 - Dust Tight, Waterproof
	Features	Epoxy Sealed Terminals
Report errors?	Panel Cutout Dimensions	Circular - 13.60mm Dia
1		Report errors?

IPC1SAD1L0G Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

IPC1SAD1L0G Payment Methods



IPC1SAD1L0G Shipping Methods



If you have any question about IPC1SAD1L0G, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com