

IPD2012-760 Information

ww.helsener.com

Part Number IPD2012-760
Manufacturer Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description 20 WATT DESKTOP POWER SUPPLY 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IPD2012-760 Specifications

Manufacturer Part NumberIPD2012-760ManufacturerInventus PowerCategoryPower Supplies - External/Internal (Off-Board)Package-SeriesIPD20Region UtilizedNorth AmericaFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input85 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.6APower (Watts)19WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 60°C		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series IPD20 Region Utilized North America Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI	Manufacturer Part Number	IPD2012-760
Package - Series IPD20 Region Utilized North America Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI	Manufacturer	Inventus Power
Package - IPD20 Region Utilized North America Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI	Category	Power Supplies - External/Internal (Off-Board)
SeriesIPD20Region UtilizedNorth AmericaFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input85 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.6APower (Watts)19WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI		AC DC Desktop, Wall Adapters
Region Utilized North America Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption 100mW (Max) Polarization Applications ITE (Commercial) Efficiency Level VI	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI	Series	IPD20
Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI	Region Utilized	North America
Voltage - Input85 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.6APower (Watts)19WNo Load Power Consumption100mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VI	Form	Desktop (Class I)
Voltage - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI	Input Type	Cord (Sold Separately)
Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI	Voltage - Input	85 ~ 264 VAC
Power (Watts) No Load Power Consumption 100mW (Max) Polarization Applications ITE (Commercial) Efficiency Level VI	Voltage - Output	12V
No Load Power Consumption 100mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI	Current - Output (Max)	1.6A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level VI	Power (Watts)	19W
Applications ITE (Commercial) Efficiency Level VI	No Load Power Consumption	100mW (Max)
Efficiency Level VI	Polarization	Positive Center
•	Applications	ITE (Commercial)
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$	Efficiency	Level VI
	Operating Temperature	0°C ~ 60°C
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Size / Dimension 3.53" L x 1.92" W x 0.99" H (89.6mm x 48.8mm x 25.2mm)	Size / Dimension	3.53" L x 1.92" W x 0.99" H (89.6mm x 48.8mm x 25.2mm)
Report errors?		Report errors?

IPD2012-760 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IPD2012-760 Payment Methods



















IPD2012-760 Shipping Methods













If you have any question about IPD2012-760, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com