

IPS-G1003-6 Information



For Reference Only

Part Number IPS-G1003-6 **Manufacturer** Cynergy 3

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESSURE 0-100BARG 0-5V

Package Cylinder

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IPS-G1003-6 Specifications

Manufacturer Part Number IPS-G1003-6 Manufacturer Cynergy 3 Category Sensors, Transducers Package Cylinder Series IPS Pressure Type Vented Gauge Operating Pressure 14.5 PSI (100 kPa) Output Type Analog Voltage Output 0 V ~ 5 V Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -20°C ~ 135°C Package / Case Cylinder Supplier Device Package -		
Category Sensors, Transducers Pressure Sensors, Transducers Package Cylinder Series IPS Pressure Type Vented Gauge Operating Pressure 14.5 PSI (100 kPa) Output Type Analog Voltage Output 0 V ~ 5 V Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -20°C ~ 135°C Package / Case Cylinder	Manufacturer Part Number	IPS-G1003-6
Pressure Sensors, Transducers Package Cylinder Series IPS Pressure Type Vented Gauge Operating Pressure 14.5 PSI (100 kPa) Output Type Analog Voltage Output 0 V ~ 5 V Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -20°C ~ 135°C Package / Case Cylinder	Manufacturer	Cynergy 3
PackageCylinderSeriesIPSPressure TypeVented GaugeOperating Pressure14.5 PSI (100 kPa)Output TypeAnalog VoltageOutput0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 135°CPackage / CaseCylinder	Category	Sensors, Transducers
SeriesIPSPressure TypeVented GaugeOperating Pressure14.5 PSI (100 kPa)Output TypeAnalog VoltageOutput0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 135°CPackage / CaseCylinder		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 14.5 PSI (100 kPa) Output Type Analog Voltage Output 0 V ~ 5 V Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -20°C ~ 135°C Package / Case Cylinder	Package	Cylinder
$\begin{array}{llllllllllllllllllllllllllllllllllll$	Series	IPS
Output TypeAnalog VoltageOutput $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $9 \text{ V} \sim 32 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure $29.01 \text{ PSI } (200 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 135^{\circ}\text{C}$ Package / CaseCylinder	Pressure Type	Vented Gauge
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $9 \text{ V} \sim 32 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure $29.01 \text{ PSI } (200 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 135^{\circ}\text{C}$ Package / CaseCylinder	Operating Pressure	14.5 PSI (100 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $9 \text{ V} \sim 32 \text{ V}$ Port Size $Male - 1/4" (6.35\text{mm}) \text{ BSP}$ Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$ Termination Style $Connector$ Maximum Pressure $29.01 \text{ PSI } (200 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 135^{\circ}\text{C}$ Package / Case $Cylinder$	Output Type	Analog Voltage
Voltage - Supply $9 \text{ V} \sim 32 \text{ V}$ Port Size $Male - 1/4$ " (6.35mm) BSP Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$ Termination Style $Connector$ Maximum Pressure $29.01 \text{ PSI } (200 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 135^{\circ}\text{C}$ Package / Case $Cylinder$	Output	0 V ~ 5 V
Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -20°C ~ 135°C Package / Case Cylinder	Accuracy	±0.25%
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -20°C ~ 135°C Package / Case Cylinder	Voltage - Supply	9 V ~ 32 V
Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -20°C ~ 135°C Package / Case Cylinder	Port Size	Male - 1/4" (6.35mm) BSP
Termination Style Connector Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature $-20^{\circ}\text{C} \sim 135^{\circ}\text{C}$ Package / Case Cylinder	Port Style	Threaded
Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -20°C ~ 135°C Package / Case Cylinder	Features	Amplified Output, Temperature Compensated
Operating Temperature -20°C ~ 135°C Package / Case Cylinder	Termination Style	Connector
Package / Case Cylinder	Maximum Pressure	29.01 PSI (200 kPa)
	Operating Temperature	-20°C ~ 135°C
Supplier Device Package -	Package / Case	Cylinder
	Supplier Device Package	-
Report errors?		Report errors?

IPS-G1003-6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IPS-G1003-6 Payment Methods



















IPS-G1003-6 Shipping Methods













If you have any question about IPS-G1003-6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com