

# IPS-G2503-6

### **IPS-G2503-6 Information**



### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **IPS-G2503-6 Specifications**

ManufacturerCynergy 3CategorySensors, TransducersPackagePressure Sensors, TransducersPackageCylinderSeriesIPSPressure TypeVented GaugeOperating PressureSel. 250 pSI (2500 kPa)Output TypeAnalog VoltageOutput Type0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort SyleConnectorFeaturesConnectorMaximum Pressure-Operating Temperature-Operating Temperature-Operat		
CategorySensors, TransducersPressure Sensors, TransducersPackageCylinderSeriesIPSPressure TypeVented GaugeOperating Pressure362.59 PSI (2500 kPa)Output TypeAnalog VoltageOutput Type0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Operating Temperature-0°C ~ 135°CPackage / CaseCylinder	Manufacturer Part Number	IPS-G2503-6
Pressure Sensors, TransducersPackageCylinderSeriesIPSPressure TypeVented GaugeOperating Pressure362.59 PSI (2500 kPa)Output TypeAnalog VoltageOutput0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort SyleThreadedFeaturesAmplified Output, Temperature CompensatedGunector-Operating Temperature-Operating Temperature-Operating Temperature-Operating TemperatureCylinderPackage / CaseCylinder	Manufacturer	Cynergy 3
PackageCylinderSeriesIPSPressure TypeVented GaugeOperating Pressure362.59 PSI (2500 kPa)Output TypeAnalog VoltageOutput Type0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleConnectorFeaturesAmplified Output, Temperature CompensatedMaximum Pressure-Operating Temperature-20°C ~ 135°CPackage / CaseCylinder	Category	Sensors, Transducers
SeriesIPSPressure TypeVented GaugeOperating Pressure362.59 PSI (2500 kPa)Output TypeAnalog VoltageOutput0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Operating Temperature-20°C ~ 135°CPackage / CaseCylinder		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure362.59 PSI (2500 kPa)Output TypeAnalog VoltageOutput0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Operating Temperature-20°C ~ 135°CPackage / CaseCylinder	Package	Cylinder
Operating Pressure362.59 PSI (2500 kPa)Output TypeAnalog VoltageOutput0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Operating Temperature-Operating Temperature-20°C ~ 135°CPackage / CaseCylinder	Series	IPS
Output TypeAnalog VoltageOutput0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Operating Temperature-20°C ~ 135°CPort Stage / CaseCylinder	Pressure Type	Vented Gauge
Output0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-20°C ~ 135°CPackage / CaseCylinder	Operating Pressure	362.59 PSI (2500 kPa)
Acuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-20°C ~ 135°CPackage / CaseCylinder	Output Type	Analog Voltage
Yoltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-20°C ~ 135°CPackage / CaseCylinder	Output	0 V ~ 5 V
Port SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-20°C ~ 135°CPackage / CaseCylinder	Accuracy	±0.25%
Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-0°C ~ 135°CPackage / CaseCylinder	Voltage - Supply	9 V ~ 32 V
FeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-20°C ~ 135°CPackage / CaseCylinder	Port Size	Male - 1/4" (6.35mm) BSP
Termination StyleConnectorMaximum Pressure-Operating Temperature-20°C ~ 135°CPackage / CaseCylinder	Port Style	Threaded
Maximum Pressure-Operating Temperature-20°C ~ 135°CPackage / CaseCylinder	Features	Amplified Output, Temperature Compensated
Operating Temperature-20°C ~ 135°CPackage / CaseCylinder	Termination Style	Connector
Package / Case Cylinder	Maximum Pressure	-
	Operating Temperature	-20°C ~ 135°C
Sumplier Device Package -	Package / Case	Cylinder
Supprier Device Fuckage	Supplier Device Package	-
Report errors?		Report errors?

#### **IPS-G2503-6** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE SUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about IPS-G2503-6, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com