

IPS-G4003-6 Information



For Reference Only

Part Number IPS-G4003-6 **Manufacturer** Cynergy 3

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESSURE 0-400BARG 0-5V

Package Cylinde

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IPS-G4003-6 Specifications

Manufacturer Part Number IPS-G4003-6 Manufacturer Cynergy 3 Category Sensors, Transducers Package Cylinder Series IPS Pressure Type Vented Gauge Operating Pressure 580.15 PSI (4000 kPa) Output Type Analog Voltage Output 0 V ~ 5 V Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -20°C ~ 135°C Package / Case Cylinder Supplier Device Package -		
CategorySensors, TransducersPackageCylinderSeriesIPSPressure TypeVented GaugeOperating Pressure580.15 PSI (4000 kPa)Output TypeAnalog VoltageOutput0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-20°C ~ 135°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	IPS-G4003-6
Package Cylinder Series IPS Pressure Type Vented Gauge Operating Pressure Operating Pressure Output Type Analog Voltage Output 0 V ~ 5 V Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure Operating Temperature -20°C ~ 135°C Package / Case Cylinder Supplier Device Package Cented Gauge Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder Cylinder	Manufacturer	Cynergy 3
PackageCylinderSeriesIPSPressure TypeVented GaugeOperating Pressure580.15 PSI (4000 kPa)Output TypeAnalog VoltageOutput0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-20°C ~ 135°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesIPSPressure TypeVented GaugeOperating Pressure580.15 PSI (4000 kPa)Output TypeAnalog VoltageOutput0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-20°C ~ 135°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure580.15 PSI (4000 kPa)Output TypeAnalog VoltageOutput0 V ~ 5 VAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-20°C ~ 135°CPackage / CaseCylinderSupplier Device Package-	Package	Cylinder
Operating Pressure 580.15 PSI (4000 kPa) Output Type Analog Voltage Output 0 V ~ 5 V Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure Operating Temperature -20°C ~ 135°C Package / Case Supplier Device Package - Cuthout Analog Voltage Analog Voltage - 0 V ~ 5 V Accuracy ±0.25% Analog Voltage 40.25% Confector Analog Voltage - Cox 32 V Accuracy - 40.25% Accuracy - 500 C ~ 135°C Cylinder Supplier Device Package	Series	IPS
Output TypeAnalog VoltageOutput $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $9 \text{ V} \sim 32 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature $-20^{\circ}\text{C} \sim 135^{\circ}\text{C}$ Package / CaseCylinderSupplier Device Package-	Pressure Type	Vented Gauge
Output $0 \text{ V} \sim 5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $9 \text{ V} \sim 32 \text{ V}$ Port Size $\text{Male - 1/4" (6.35mm) BSP}$ Port Style Threaded Features $\text{Amplified Output, Temperature Compensated}$ Termination Style Connector Maximum Pressure $-$ Operating Temperature $-20^{\circ}\text{C} \sim 135^{\circ}\text{C}$ Package / Case Cylinder Supplier Device Package $-$	Operating Pressure	580.15 PSI (4000 kPa)
Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -20°C ~ 135°C Package / Case Cylinder Supplier Device Package -	Output Type	Analog Voltage
Voltage - Supply Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -20°C ~ 135°C Package / Case Cylinder Supplier Device Package -	Output	0 V ~ 5 V
Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -20°C ~ 135°C Package / Case Cylinder Supplier Device Package -	Accuracy	±0.25%
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -20°C ~ 135°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	9 V ~ 32 V
Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -20°C ~ 135°C Package / Case Cylinder Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) BSP
Termination Style Connector Maximum Pressure - Operating Temperature -20°C ~ 135°C Package / Case Cylinder Supplier Device Package -	Port Style	Threaded
Maximum Pressure - Operating Temperature -20°C ~ 135°C Package / Case Cylinder Supplier Device Package -	Features	Amplified Output, Temperature Compensated
Operating Temperature -20°C ~ 135°C Package / Case Cylinder Supplier Device Package -	Termination Style	Connector
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-20°C ~ 135°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

IPS-G4003-6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IPS-G4003-6 Payment Methods



















IPS-G4003-6 Shipping Methods













If you have any question about IPS-G4003-6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com