



IPSAT-G2503-5 Information

Heisener.com

Part Number IPSAT-G2503-5

Manufacturer Cynergy 3

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE TRANS 0-250BARG 4-20MA

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









IPSAT-G2503-5 Specifications

Manufacturer Part NumberIPSAT-G2503-5ManufacturerCynergy 3CategorySensors, TransducersPackage-SeriesIPSATPressure TypeGaugeOperating Pressure3625.94 PSI (25000 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure5801.5 PSI (40000 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-Report errors?			
Category Sensors, Transducers Pressure Sensors, Transducers Package - Series IPSAT Pressure Type Gauge Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure Supply 10 Connector Supplier Device Package - Supplier Device Package - Supplier Device Package - Supplier Device Package	Manufacturer Part Number	IPSAT-G2503-5	
Pressure Sensors, Transducers Package Series IPSAT Pressure Type Gauge Operating Pressure 3625.94 PSI (25000 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure 5801.5 PSI (40000 kPa) Operating Temperature -20°C ~ 75°C Package / Case Supplier Device Package -	Manufacturer	Cynergy 3	
Package - IPSAT Pressure Type Gauge Operating Pressure 3625.94 PSI (25000 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 5801.5 PSI (40000 kPa) Operating Temperature - 20°C ~ 75°C Package / Case - Supplier Device Package	Category	Sensors, Transducers	
SeriesIPSATPressure TypeGaugeOperating Pressure3625.94 PSI (25000 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply10 V ~ 28 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure5801.5 PSI (40000 kPa)Operating Temperature-20°C ~ 75°CPackage / Case-Supplier Device Package-		Pressure Sensors, Transducers	
Pressure Type Gauge Operating Pressure 3625.94 PSI (25000 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 5801.5 PSI (40000 kPa) Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Package	-	
Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 5801.5 PSI (40000 kPa) Operating Temperature -20°C ~ 75°C Package / Case Supplier Device Package -	Series	IPSAT	
Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 5801.5 PSI (40000 kPa) Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Pressure Type	Gauge	
Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 5801.5 PSI (40000 kPa) Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Operating Pressure	3625.94 PSI (25000 kPa)	
Accuracy ±0.25% Voltage - Supply 10 V ~ 28 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 5801.5 PSI (40000 kPa) Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Output Type	Analog Current	
Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 5801.5 PSI (40000 kPa) Operating Temperature -20°C ~ 75°C Package / Case Supplier Device Package -	Output	4 mA ~ 20 mA	
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 5801.5 PSI (40000 kPa) Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Accuracy	±0.25%	
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 5801.5 PSI (40000 kPa) Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Voltage - Supply	10 V ~ 28 V	
Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 5801.5 PSI (40000 kPa) Operating Temperature -20°C ~ 75°C Package / Case Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) NPT	
Termination Style Connector Maximum Pressure $5801.5 \text{ PSI } (40000 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$ Package / Case - Supplier Device Package -	Port Style	Threaded	
Maximum Pressure $5801.5 \text{ PSI } (40000 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 75^{\circ}\text{C}$ Package / Case-Supplier Device Package-	Features	Amplified Output, Temperature Compensated	
Operating Temperature -20°C ~ 75°C Package / Case - Supplier Device Package -	Termination Style	Connector	
Package / Case - Supplier Device Package -	Maximum Pressure	5801.5 PSI (40000 kPa)	
Supplier Device Package -	Operating Temperature	-20°C ~ 75°C	
	Package / Case	-	
Report errors?	Supplier Device Package	-	
			Report errors?

IPSAT-G2503-5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

IPSAT-G2503-5 Payment Methods



















IPSAT-G2503-5 Shipping Methods













If you have any question about IPSAT-G2503-5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com