

## **IPSL-G0250-5 Information**

Part Number IPSL-G0250-5 Manufacturer Cynergy 3

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR PRESSURE 0-.25BARG 4-20MA

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **IPSL-G0250-5 Specifications**

Manufacturer Part Number       IPSL-G0250-5         Manufacturer       Cynergy 3         Category       Sensors, Transducers         Package       Cylinder         Series       IPSL         Pressure Type       Vented Gauge         Operating Pressure       3.63 PSI (25 kPa)         Output Type       Analog Current         Output       4mA ~ 20mA         Accuracy       ±0.25%         Voltage - Supply       9 V ~ 32 V         Port Size       Male - 1/4" (6.35mm) BSP         Port Style       Threaded         Features       Amplified Output, Temperature Compensated         Termination Style       Connector         Maximum Pressure       29.01 PSI (200 kPa)         Operating Temperature       -20°C ~ 80°C         Package / Case       Cylinder         Supplier Device Package       -         Report errors?		
CategorySensors, TransducersPackageCylinderSeriesIPSLPressure TypeVented GaugeOperating Pressure3.63 PSI (25 kPa)Output TypeAnalog CurrentOutput4mA ~ 20mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	IPSL-G0250-5
Package Cylinder  Series IPSL  Pressure Type Vented Gauge Operating Pressure Output Type Analog Current Output 4mA ~ 20mA Accuracy ±0.25% Voltage - Supply 9 V ~ 32 V Port Size Male - 1/4" (6.35mm) BSP Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature - 20°C ~ 80°C Package / Case Cylinder Supplier Device Package	Manufacturer	Cynergy 3
PackageCylinderSeriesIPSLPressure TypeVented GaugeOperating Pressure3.63 PSI (25 kPa)Output TypeAnalog CurrentOutput4mA ~ 20mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesIPSLPressure TypeVented GaugeOperating Pressure3.63 PSI (25 kPa)Output TypeAnalog CurrentOutput4mA ~ 20mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure3.63 PSI (25 kPa)Output TypeAnalog CurrentOutput4mA ~ 20mAAccuracy±0.25%Voltage - Supply9 V ~ 32 VPort SizeMale - 1/4" (6.35mm) BSPPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Package	Cylinder
Operating Pressure  3.63 PSI (25 kPa)  Output Type  Analog Current  4mA ~ 20mA  Accuracy  ±0.25%  Voltage - Supply  Port Size  Male - 1/4" (6.35mm) BSP  Port Style  Features  Amplified Output, Temperature Compensated  Termination Style  Connector  Maximum Pressure  29.01 PSI (200 kPa)  Operating Temperature  -20°C ~ 80°C  Package / Case  Supplier Device Package  -	Series	IPSL
Output Type  Output  4mA ~ 20mA  Accuracy  ±0.25%  Voltage - Supply  Port Size  Male - 1/4" (6.35mm) BSP  Port Style  Features  Amplified Output, Temperature Compensated  Termination Style  Maximum Pressure  29.01 PSI (200 kPa)  Operating Temperature  -20°C ~ 80°C  Package / Case  Supplier Device Package  -  Analog Current  4mA ~ 20mA  50 C  Contage / Case  Cylinder	Pressure Type	Vented Gauge
Output 4mA ~ 20mA  Accuracy ±0.25%  Voltage - Supply 9 V ~ 32 V  Port Size Male - 1/4" (6.35mm) BSP  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Connector  Maximum Pressure 29.01 PSI (200 kPa)  Operating Temperature -20°C ~ 80°C  Package / Case Cylinder  Supplier Device Package -	Operating Pressure	3.63 PSI (25 kPa)
Accuracy ±0.25%  Voltage - Supply 9 V ~ 32 V  Port Size Male - 1/4" (6.35mm) BSP  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Connector  Maximum Pressure 29.01 PSI (200 kPa)  Operating Temperature -20°C ~ 80°C  Package / Case Cylinder  Supplier Device Package -	Output Type	Analog Current
Voltage - Supply  Port Size  Male - 1/4" (6.35mm) BSP  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  Connector  Maximum Pressure  29.01 PSI (200 kPa)  Operating Temperature  -20°C ~ 80°C  Package / Case  Cylinder  Supplier Device Package  -	Output	4mA ~ 20mA
Port Size Male - 1/4" (6.35mm) BSP  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Connector  Maximum Pressure 29.01 PSI (200 kPa)  Operating Temperature -20°C ~ 80°C  Package / Case Cylinder  Supplier Device Package -	Accuracy	±0.25%
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure 29.01 PSI (200 kPa) Operating Temperature -20°C ~ 80°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	9 V ~ 32 V
Features Amplified Output, Temperature Compensated  Termination Style Connector  Maximum Pressure 29.01 PSI (200 kPa)  Operating Temperature -20°C ~ 80°C  Package / Case Cylinder  Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) BSP
Termination Style Connector  Maximum Pressure 29.01 PSI (200 kPa)  Operating Temperature -20°C ~ 80°C  Package / Case Cylinder  Supplier Device Package -	Port Style	Threaded
Maximum Pressure29.01 PSI (200 kPa)Operating Temperature-20°C ~ 80°CPackage / CaseCylinderSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature -20°C ~ 80°C  Package / Case Cylinder  Supplier Device Package -	Termination Style	Connector
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	29.01 PSI (200 kPa)
Supplier Device Package -	Operating Temperature	-20°C ~ 80°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

#### **IPSL-G0250-5 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **IPSL-G0250-5 Payment Methods**





















## **IPSL-G0250-5 Shipping Methods**













If you have any question about IPSL-G0250-5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com